


MIKROELEKTRONIKA D.O.O, Batajnički drum 23, 11000 Belgrade, Serbia VAT: SR105917343 Registration No. 20490918
Phone: + 381 11 78 57 600 Fax: + 381 11 63 09 644 E-mail: office@mikroe.com

www.mikroe.com

## 6DOF IMU 12 Click





PID: MIKROE-4073

**6DOF IMU 12 Click** carries the ultra-low-power <u>BMI270</u> from <u>Bosch Sensortec</u>, inertial measurement unit optimized for wearables providing precise acceleration, angular rate measurement and intelligent on-chip motion-triggered interrupt features. The 6-axis sensor combines a 16-bit tri-axial gyroscope and a 16-bit tri-axial accelerometer featuring Bosch's automotive-proven gyroscope technology. The BMI270 includes several functionalities such as an integrated plug-and-play step counter/detector for wrist-worn devices. Moreover, the IMU is suitable for hearables, smart clothes, smart shoes, smart glasses and ankle bands.

6DOF IMU 12 Click is supported by a mikroSDK compliant library, which includes functions that simplify software development. This Click board<sup>™</sup> comes as a fully tested product, ready to be used on a system equipped with the mikroBUS<sup>™</sup> socket.

Mikroe produces entire development toolchains for all major microcontroller architectures.

Committed to excellency, we are dedicated to helping engineers bring the project development up to speed and achieve outstanding results.





health and safety management system.



MIKROELEKTRONIKA D.O.O, Batajnički drum 23, 11000 Belgrade, Serbia VAT: SR105917343 Registration No. 20490918
Phone: + 381 11 78 57 600 Fax: + 381 11 63 09 644 E-mail: office@mikroe.com

www.mikroe.com

## **Specifications**

Туре	Acceleration, Gyroscope, Motion
Applications	An ideal choice for wearables, hearables, smart clothing, augmented / virtual reality.
On-board modules	6DOF IMU 12 Click uses the BMI270 IC, a low power inertial measurement unit, from Bosch Sensortec.
Key Features	16-bit triaxial gyroscope and a 16-bit triaxial accelerometer, ensuring post-soldering sensitivity errors down to $\pm$ 0.4%.
Interface	I2C,SPI
ClickID	No
Compatibility	mikroBUS
Click board size	M (42.9 x 25.4 mm)
Input Voltage	3.3V

## **Resources**

mikroBUS™

**mikroSDK** 

**mikroSDK** 

Click Boards™


## **Downloads**

6DOF IMU 12 click schematic

6DOF IMU 12 click example on Libstock

6DOF IMU 12 click 2D and 3D files

**BMI270 datasheet** 







health and safety management system.