

RFID 2 Click



PID: MIKROE-4208

RFID 2 Click is a compact add-on board that contains a stand-alone RFID reader with a built-in antenna easy-to-use for embedded applications. This board features the [ID-12LA-SA](#), an advanced low-cost RFID reader module usable with 38 different tags from [ID Innovations](#). This small 125kHz reader has a 9600bps TTL/RS232 output with Magnetic, Wiegand, or ASCII format, read ranges of 12cm and 18cm, and possesses a remotely controlled channel that can be used to operate with user peripherals. This Click board™ is designed to be used in stand-alone or remote-controlled applications to identify and track tags attached to objects.

RFID 2 Click is supported by a mikroSDK compliant library, which includes functions that simplify software development. This Click board™ comes as a fully tested product, ready to be used on a system equipped with the mikroBUS™ socket.

Mikroe produces entire development toolchains for all major microcontroller architectures.

Committed to excellency, we are dedicated to helping engineers bring the project development up to speed and achieve outstanding results.



ISO 27001: 2013 certification of informational security management system.
 ISO 14001: 2015 certification of environmental management system.
 OHSAS 18001: 2008 certification of occupational health and safety management system.



ISO 9001: 2015 certification of quality management system (QMS).

Specifications

Type	RFID/NFC
Applications	Can be used in stand-alone or remote-controlled applications to identify and track tags attached to objects.
On-board modules	RFID 2 Click is based on the ID-12LA-SA, an advanced low-cost RFID reader module designed to be used in stand-alone or remote-controlled applications to identify and track tags attached to objects from ID Innovations.
Key Features	Low power consumption, autonomous mode, remote controlled auxiliary Channel, long range 12cm and 18cm, and more.
Interface	UART
ClickID	No
Compatibility	mikroBUS
Click board size	L (57.15 x 25.4 mm)
Input Voltage	3.3V or 5V

Resources

[mikroBUS™](#)

[mikroSDK](#)

[Click board™ Catalog](#)

[Click boards™](#)

Downloads

[NE555 datasheet](#)

[RFID 2 click 2D and 3D files](#)

[RFID 2 click schematic](#)

[RFID 2 click example on Libstock](#)

[ID-12LA-SA datasheet](#)

Mikroe produces entire development toolchains for all major microcontroller architectures.

Committed to excellency, we are dedicated to helping engineers bring the project development up to speed and achieve outstanding results.



ISO 27001: 2013 certification of informational security management system.
 ISO 14001: 2015 certification of environmental management system.
 OHSAS 18001: 2008 certification of occupational health and safety management system.



ISO 9001: 2015 certification of quality management system (QMS).