MIKROELEKTRONIKA D.O.O, Batajnički drum 23, 11000 Belgrade, Serbia VAT: SR105917343 Registration No. 20490918

Phone: + 381 11 78 57 600 Fax: + 381 11 63 09 644 E-mail: office@mikroe.com

Brushless 9 Click





PID: MIKROE-4387

Brushless 9 Click is a compact add-on board suitable for controlling BLDC motors with any MCU. This board features the TC78B027FTG, a 1-Hall sine-wave PWM controller for three-phase brushless DC motors from <u>Toshiba Semiconductor</u>. It simplifies the motor selection by using only one Hall sensor input that can be used with either a single Hall sensor motor or the more conventional 3 Hall sensor motors. Besides, it offers energy-saving and quiet motor operation, alongside incorporated non-volatile memory and a closed-loop speed control function. This Click board™ provides optimum operating efficiency in applications such as high-velocity server fans, blowers, and pumps.

Brushless 9 Click is supported by a mikroSDK compliant library, which includes functions that simplify software development. This Click board $^{\text{\tiny M}}$ comes as a fully tested product, ready to be used on a system equipped with the mikroBUS $^{\text{\tiny M}}$ socket.

Mikroe produces entire development toolchains for all major microcontroller architectures.

Committed to excellency, we are dedicated to helping engineers bring the project development up to speed and achieve outstanding results.





health and safety management system.



MIKROELEKTRONIKA D.O.O, Batajnički drum 23, 11000 Belgrade, Serbia VAT: SR105917343 Registration No. 20490918 Phone: + 381 11 78 57 600 Fax: + 381 11 63 09 644 E-mail: office@mikroe.com www.mikroe.com

Specifications

Туре	Brushless
Applications	Can be used in applications such as high- velocity server fans, blowers, and pumps.
On-board modules	Brushless 9 Click is based on the TC78B027FTG, a 1-Hall sine-wave PWM controller for three-phase brushless DC motors from Toshiba Semiconductor.
Key Features	1-Hall sine-wave PWM drive, closed loop speed control, output RPM information, protection features, and more.
Interface	GPIO
ClickID	No
Compatibility	mikroBUS
Click board size	L (57.15 x 25.4 mm)
Input Voltage	3.3V or 5V

Resources

<u>mikroBUS™</u>

mikroSDK

Click board™ Catalog

Click boards™

Downloads

Brushless 9 click 2D and 3D files

TC78B027FTG datasheet

Brushless 9 click schematic

SSM6K513NU datasheet

Brushless 9 click example on Libstock

Mikroe produces entire development toolchains for all major microcontroller architectures.

Committed to excellency, we are dedicated to helping engineers bring the project development up to speed and achieve outstanding results.





health and safety management system.