

Time-saving embedded tools

MIKROELEKTRONIKA D.O.O, Batajnički drum 23, 11000 Belgrade, Serbia VAT: SR105917343 Registration No. 20490918 Phone: + 381 11 78 57 600 Fax: + 381 11 63 09 644 E-mail: office@mikroe.com www.mikroe.com

EEPROM 9 Click





PID: MIKROE-5681

EEPROM 9 Click is a compact add-on board with a highly reliable nonvolatile memory solution. This board features the M95P32-I, the 32Mbit electrically erasable programmable memory with enhanced hardware write protection from STMicroelectronics. The M95P32-I is internally organized as 8192 programmable pages of 512 bytes each, accessed through the SPI interface. It combines unprecedented data storage with byte flexibility, page alterability, high page cycling performance, and ultra-low power consumption. It lasts 500k write cycles with 100 years of data retention (10 years after 500k cycles). This Click board[™] is suitable for various consumer and industrial applications where dependable nonvolatile memory storage is essential.

EEPROM 9 Click is supported by a <u>mikroSDK</u> compliant library, which includes functions that simplify software development. This <u>Click board</u> comes as a fully tested product, ready to be used on a system equipped with the <u>mikroBUS</u> socket.

Mikroe produces entire development toolchains for all major microcontroller architectures.

Committed to excellency, we are dedicated to helping engineers bring the project development up to speed and achieve outstanding results.



ISO 27001: 2013 certification of informational security management system. ISO 14001: 2015 certification of environmental management system. OHSAS 18001: 2008 certification of occupational health and safety management system.



ISO 9001: 2015 certification of quality management system (QMS).



MIKROELEKTRONIKA D.O.O, Batajnički drum 23, 11000 Belgrade, Serbia VAT: SR105917343 Registration No. 20490918 Phone: + 381 11 78 57 600 Fax: + 381 11 63 09 644 E-mail: office@mikroe.com www.mikroe.com

Specifications

Туре	EEPROM
Applications	Can be used for various consumer and industrial applications
On-board modules	M95P32-I - 32Mbit of page EEPROM from STMicroelectronics
Key Features	Fast read via SPI interface, ultra low power consumption, write endurance and data retention, high write/erase performance, write protection, communication hold function, and more
Interface	SPI
ClickID	Yes
Compatibility	mikroBUS
Click board size	S (28.6 x 25.4 mm)
Input Voltage	3.3V

Resources

<u>mikroBUS</u>™

<u>mikroSDK</u>

Click board[™] Catalog

Click Boards™

ClickID

Downloads

EEPROM 9 click example on Libstock

EEPROM 9 click 2D and 3D files

M95P32-I datasheet

EEPROM 9 click schematic

Mikroe produces entire development toolchains for all major microcontroller architectures.

Committed to excellency, we are dedicated to helping engineers bring the project development up to speed and achieve outstanding results.



ISO 27001: 2013 certification of informational security management system. ISO 14001: 2015 certification of environmental management system. OHSAS 18001: 2008 certification of occupational health and safety management system.



ISO 9001: 2015 certification of quality management system (QMS).