

## NL8MMXX

8 pole speakON feedthrough coupler for cable extensions



## Technical Information

| Product                |         |
|------------------------|---------|
| <b>Title</b>           | NL8MMXX |
| <b>Connection Type</b> | Adapter |
| <b>Gender</b>          | male    |

| Electrical                       |  |
|----------------------------------|--|
| <b>Contact resistance</b>        | < 3 mΩ   |
| <b>Dielectric strength</b>       | 1.5 kVac   |
| <b>Insulation resistance</b>     | > 0.1 GΩ (after dampheat)  |
| <b>Rated current per contact</b> | 25 A rms continuous  |
| <b>Rated voltage</b>             | 250 V ac   |
| <b>Attention</b>                 | speakON is NOT to be used as an mains or power supply connector (AC / DC)! |

| Mechanical            |                      |
|-----------------------|----------------------|
| <b>Lifetime</b>       | > 5000 mating cycles |
| <b>Locking device</b> | Quick Lock           |

| Material               |                                   |
|------------------------|-----------------------------------|
| <b>Contact plating</b> | Ag                                |
| <b>Contacts</b>        | Copper Alloy                      |
| <b>Shell</b>           | Zinc diecast, black chrome plated |
| <b>Insert</b>          | Polyamide (PA 6.6)                |

| Environmental            |                  |
|--------------------------|------------------|
| <b>Temperature range</b> | -30 °C to +80 °C |
| <b>Flammability</b>      | UL 94 V-0        |