



## **NLT4MXX-BAG**

4 pole male cable connector, black metal housing, chuck type strain relief

This connector is fully compliant to the device standard IEC 62368-1, due to its component certification according to IEC 61984.

The speakON STXX Series was especially designed for heavy duty amplifier-loudspeaker applications like professional touring. The extremely rugged and durable STXX Series features an all metal housing.

## **Features & Benefits**

- IEC 61984 certified, IEC 62368-1 compliant
- Uses precise "Quick Lock" system
- Weatherproof built-in gasket meets IP
  54 protection class in mated condition

- Extremely robust metal housing and glass reinforced V-0 material insert designed for harsh and demanding environment
- Extra large solder contacts for up to 6 mm<sup>2</sup> (AWG 10) wires



## **Technical Information**

Product	
Title	NLT4MXX-BAG
Gender	male

Electrical	
Contact resistance	< 2 mΩ
Dielectric strength	2.8 kVac
Insulation resistance	>0.1 G $\Omega$ (after dampheat)
Rated current per contact	30 A rms continuous
Rated voltage	250 V ac
Attention	speakON is NOT to be used as an AC mains or power supply connector!

Mechanical	
Cable O.D.	9 - 16 mm
Lifetime	> 5000 mating cycles
Wiresize	6 mm²
Wiresize	10 AWG
Termination	Solder contacts
Locking device	Quick Lock