



NLT8MXX-BAG

8 pole male cable connector, black metal housing, chuck type strain relief, 1/4" flat tabs

This connector is accepted within audio equipment designed according to IEC 62368-1 due to its component certification according to IEC 61984.

The speakON STXX Series was especially designed for heavy duty amplifier-loudspeaker applications like professional touring. The extremely rugged and durable STXX Series features an all metal housing.

- IEC 61984 certified, thus accepted as a component of equipment acc. to IEC 62368-1
- Current rating 30 A rms
- Extremely robust metal housing and glass reinforced V-0 material insert designed for harsh and demanding environment
- Precise "Quick Lock" system
- Compatible with complete speakON 8 pole product series

Technical Information

| Product | |
|---------|-------------|
| Title | NLT8MXX-BAG |
| Gender | male |

| Electrical | |
|---------------------------|--|
| Contact resistance | < 2 mΩ |
| Dielectric strength | 1.5 kVac |
| Insulation resistance | > 0.1 GΩ (after dampheat) |
| Rated current per contact | 30 A rms continuous (acc. to IEC 61984) |
| Rated voltage | 250 V ac |
| Attention | speakON is NOT to be used as an mains or power supply connector (AC / DC)! |

| Mechanical | |
|-----------------|--|
| Cable O.D. | 8 - 20 mm |
| Cable retention | ≥ 220 N (subject to cable O.D. and material) |
| Lifetime | > 5000 mating cycles |
| Wiresize | 1.5 mm ² - 6 mm ² |
| Wiresize | 10 AWG |
| Termination | ¼" flat tabs |
| Locking device | Quick Lock |