







# SOCKETS

SOCKETS																										
Product	Features	Accessory For																								
<p><b>OT08PC</b> Octal Socket 8-Pin</p> 	<p>8-pin 35mm DIN rail or surface mount octal socket. Rated at 10A @ 600VAC and has pressure clamp terminals.</p>	<p><b>AWG 12 to 22 (3.2 to 0.33 mm<sup>2</sup>) wire sizes. Consult individual datasheet for compatibility</b></p>																								
<p><b>NDS-8</b> Octal Socket 8-Pin Screw terminals with captive wire clamps</p> 	<p>8-pin 35mm DIN rail or surface mount octal socket. Rated at 10A @ 300VAC. Surface mounted with two #6 (M 3.5 x 0.6) screws or snaps onto a 35 mm DIN rail. A spring mechanism allows easy removal. Uses PSC8 hold-down clips.</p>	<p><b>Up to two #14 AWG (2.45 mm<sup>2</sup>) wire size</b> <b>Series:</b>  <table border="0"> <tr> <td><b>ARP</b></td> <td><b>FS500</b></td> <td><b>LLC4</b></td> <td><b>LLC5</b></td> </tr> <tr> <td><b>PRLM</b></td> <td><b>TDB</b></td> <td><b>TDBH</b></td> <td><b>TDBL</b></td> </tr> <tr> <td><b>TDI</b></td> <td><b>TDIH</b></td> <td><b>TDIL</b></td> <td><b>TDM</b></td> </tr> <tr> <td><b>TDMB</b></td> <td><b>TDMH</b></td> <td><b>TDML</b></td> <td><b>TDR</b></td> </tr> <tr> <td><b>TDS</b></td> <td><b>TDSH</b></td> <td><b>TDSL</b></td> <td><b>TRDU</b></td> </tr> <tr> <td><b>TRM</b></td> <td><b>TRS</b></td> <td><b>TRU</b></td> <td></td> </tr> </table> </p>	<b>ARP</b>	<b>FS500</b>	<b>LLC4</b>	<b>LLC5</b>	<b>PRLM</b>	<b>TDB</b>	<b>TDBH</b>	<b>TDBL</b>	<b>TDI</b>	<b>TDIH</b>	<b>TDIL</b>	<b>TDM</b>	<b>TDMB</b>	<b>TDMH</b>	<b>TDML</b>	<b>TDR</b>	<b>TDS</b>	<b>TDSH</b>	<b>TDSL</b>	<b>TRDU</b>	<b>TRM</b>	<b>TRS</b>	<b>TRU</b>	
<b>ARP</b>	<b>FS500</b>	<b>LLC4</b>	<b>LLC5</b>																							
<b>PRLM</b>	<b>TDB</b>	<b>TDBH</b>	<b>TDBL</b>																							
<b>TDI</b>	<b>TDIH</b>	<b>TDIL</b>	<b>TDM</b>																							
<b>TDMB</b>	<b>TDMH</b>	<b>TDML</b>	<b>TDR</b>																							
<b>TDS</b>	<b>TDSH</b>	<b>TDSL</b>	<b>TRDU</b>																							
<b>TRM</b>	<b>TRS</b>	<b>TRU</b>																								
<p><b>P1011-6</b> Octal Socket 8-Pin</p> 	<p>8-pin surface mount socket with binder head screw terminals. Rated at 10A @ 600VAC. UL Listed combination when used with TDM, TDB, TDS Series timers. Uses PSCRB8 hold-down brackets.</p>	<p><b>Series:</b>  <table border="0"> <tr> <td><b>ARP</b></td> <td><b>FS500</b></td> <td><b>LLC4</b></td> <td><b>LLC5</b></td> </tr> <tr> <td><b>PRLM</b></td> <td><b>TDB</b></td> <td><b>TDM</b></td> <td><b>TDMB</b></td> </tr> <tr> <td><b>TDR</b></td> <td><b>TDS</b></td> <td><b>TRB</b></td> <td><b>TRDU</b></td> </tr> <tr> <td><b>TRM</b></td> <td><b>TRS</b></td> <td><b>TRU</b></td> <td></td> </tr> </table> </p>	<b>ARP</b>	<b>FS500</b>	<b>LLC4</b>	<b>LLC5</b>	<b>PRLM</b>	<b>TDB</b>	<b>TDM</b>	<b>TDMB</b>	<b>TDR</b>	<b>TDS</b>	<b>TRB</b>	<b>TRDU</b>	<b>TRM</b>	<b>TRS</b>	<b>TRU</b>									
<b>ARP</b>	<b>FS500</b>	<b>LLC4</b>	<b>LLC5</b>																							
<b>PRLM</b>	<b>TDB</b>	<b>TDM</b>	<b>TDMB</b>																							
<b>TDR</b>	<b>TDS</b>	<b>TRB</b>	<b>TRDU</b>																							
<b>TRM</b>	<b>TRS</b>	<b>TRU</b>																								
<p><b>OT11PC</b> Magnal Socket 11-Pin</p> 	<p>Magnal Sockets are for plug-in units</p>	<p><b>11-pin Plug-in units</b> <b>Series:</b>  <table border="0"> <tr> <td><b>ARP</b></td> <td><b>LLC6</b></td> <td><b>TDB</b></td> <td><b>TDBH</b></td> </tr> <tr> <td><b>TDBL</b></td> <td><b>TDMB</b></td> <td><b>TDS</b></td> <td><b>TDSH</b></td> </tr> <tr> <td><b>TDSL</b></td> <td><b>TRB</b></td> <td><b>TRDU</b></td> <td><b>TRM</b></td> </tr> <tr> <td><b>TRS</b></td> <td><b>TRU</b></td> <td></td> <td></td> </tr> </table> </p>	<b>ARP</b>	<b>LLC6</b>	<b>TDB</b>	<b>TDBH</b>	<b>TDBL</b>	<b>TDMB</b>	<b>TDS</b>	<b>TDSH</b>	<b>TDSL</b>	<b>TRB</b>	<b>TRDU</b>	<b>TRM</b>	<b>TRS</b>	<b>TRU</b>										
<b>ARP</b>	<b>LLC6</b>	<b>TDB</b>	<b>TDBH</b>																							
<b>TDBL</b>	<b>TDMB</b>	<b>TDS</b>	<b>TDSH</b>																							
<b>TDSL</b>	<b>TRB</b>	<b>TRDU</b>	<b>TRM</b>																							
<b>TRS</b>	<b>TRU</b>																									
<p><b>SD12-PC</b> Rectangle Socket 12-pin</p> 	<p>12-pin surface Rectangle Socket.</p>	<p><b>ACBC-120</b></p>																								
<p><b>NDS-11</b> 11-pin Magnal Socket Screw terminals with captive wire clamps</p> 	<p>11 pin 35 mm DIN rail or surface mount socket. Rated at 10A @ 300VAC. Surface mounted with two #6 (M 3.5 x 0.6) screws or snaps onto a 35 mm DIN rail. A spring mechanism allows easy removal. Uses PSC11 hold-down clips.</p>	<p><b>AWG 12 to 22 (3.2 to 0.33 mm<sup>2</sup>) wire sizes</b> <b>Series:</b>  <table border="0"> <tr> <td><b>ARP</b></td> <td><b>LLC6</b></td> <td><b>TDB</b></td> <td><b>TDBH</b></td> </tr> <tr> <td><b>TDBL</b></td> <td><b>TDMB</b></td> <td><b>TDS</b></td> <td><b>TDSH</b></td> </tr> <tr> <td><b>TDSL</b></td> <td><b>TRB</b></td> <td><b>TRDU</b></td> <td><b>TRM</b></td> </tr> <tr> <td><b>TRS</b></td> <td><b>TRU</b></td> <td></td> <td></td> </tr> </table> </p>	<b>ARP</b>	<b>LLC6</b>	<b>TDB</b>	<b>TDBH</b>	<b>TDBL</b>	<b>TDMB</b>	<b>TDS</b>	<b>TDSH</b>	<b>TDSL</b>	<b>TRB</b>	<b>TRDU</b>	<b>TRM</b>	<b>TRS</b>	<b>TRU</b>										
<b>ARP</b>	<b>LLC6</b>	<b>TDB</b>	<b>TDBH</b>																							
<b>TDBL</b>	<b>TDMB</b>	<b>TDS</b>	<b>TDSH</b>																							
<b>TDSL</b>	<b>TRB</b>	<b>TRDU</b>	<b>TRM</b>																							
<b>TRS</b>	<b>TRU</b>																									