



All dimensions are in mm; tolerances according to ISO 2768 m-H

Interface

RPC-1.35 according to	IEC 61169-65
Waveguide	WR-10
Flange	UG-387/U

Material and plating

Connector parts

Center conductor
Outer conductor RPC-1.35
Coupling nut
Waveguide

Material

CuBe
Stainless steel
Stainless steel
Brass

Plating

Gold, min. 1.27 µm, over nickel
Passivated
Passivated
Gold, min. 1.27 µm, over nickel

Adaptor
RPC-1.35 Plug – Waveguide WR-10

P9S900-387

Electrical data

Impedance 50 Ω
 Frequency 75 GHz to 90 GHz
 Return loss ≥ 16 dB, 75 GHz to 90 GHz
 Insertion loss ≤ 0.7 dB, 75 GHz to 90 GHz

Mechanical data

Mating cycles RPC-1.35 ≥ 3000
 Maximum torque RPC-1.35 1.65 Nm
 Recommended torque RPC-1.35 0.90 Nm
 Recommended torque WR12 1.10 Nm
 Gauge RPC-1.35 0.003 mm to 0.050 mm

Environmental data

Temperature range - 40 °C to +85 °C
 RoHS compliant

Packing

Standard 1 pce in box
 Weight 19 g/pce

While the information has been carefully compiled to the best of our knowledge, nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. In the effort to improve our products, we reserve the right to make changes judged to be necessary.

For the installation of the electrotechnical equipment, particular electrotechnical expertise is required.



Draft	Date	Approved	Date	Rev.	Engineering change number	Name	Date
Marcel Panicke	09.01.20	Lars Ramtke	15.06.21	b00	21-1076	Marion Striegler	14.06.21

Rosenberger Hochfrequenztechnik GmbH & Co. KG P.O.Box 1260 D-84526 Tittmoning Germany www.rosenberger.de	Tel. : +49 8684 18-0 Email : info@rosenberger.de	Page 2 / 2
--	---	---------------