

PAC-400AI-C236

NEW



Feature


- Intel® Skylake C236 chipset with Xeon® CPU
- One 8 cm hot swappable fan
- Integrated one PCIe x16 and one x4 Gen3 expansion slot
- Great flexibility hardware expansion



Specifications


Model Name		PAC-400AI-C236
Chassis	Color	NAVY BLUE & BLACK
	Dimensions (WxDxH)	268.7mm x 140mm x 230.3mm
	System Fan	System Fan & CPU Fan
	Chassis Construction	Heavy duty metal
Motherboard	CPU	Intel® Xeon® E3-1275 v5 CPU (3.60 GHz, Quad Core, TDP 80W)
	Chipset	Intel® C236
	System Memory	Two 260-pin 1600/2133 MHz dual-channel DDR4 ECC and non-ECC unbuffered SODIMMs support up to 32 GB (2 x 8GB Pre-installed)
	Display Output	1 x VGA (up to 1920x1200@60 Hz) 1 x iDP interface for HDMI, LVDS, VGA, DVI, DP (up to 3840x2160@60 Hz)
Storage	Hard Drive	1x 3.5" 6 Gb/s SATA removable drive Bay (Hot swap)
	MSATA	1
I/O interfaces	Ethernet	LAN1: Intel® I219LM Clarkville-V with Intel® AMT 11.0 support LAN2: Intel® I211 PCIe controller
	KB/MS	1 x (1x6 pin)
	USB 3.2	2 x USB 3.2 Gen1
	USB 2.0	2 x USB 2.0
	Expansion	1 x PCIe Gen3 x16 slot 1 x PCIe Gen3 x4 slot **PCIe Half Size Cards length support to maximum 169mm
Power	Power Input	ATX Power (250W)
Reliability	Mounting	Wall mount
	Operating Temperature	0°C~+50°C
	Storage Temperature	0°C~+60°C
	Relative Humidity	10% ~ 95%, non-condensing
	Weight (Net/ Gross)	6 kg/7.8 kg
	Safety/EMC	CE/FCC
OS	Supported OS	Microsoft® Windows® 10, Linux

I/O Interface



PAC-400AI-C236


Dimensions (Unit: mm)



» **Single board computer in PAC-400AI (HPCIE-C236)**

Half-size PICMG 1.3 CPU Card supports LGA 1151 Intel® Xeon® E3, Core™ i3/Pentium®/Celeron® CPU with Intel® C236, ECC & non-ECC DDR4 SO-DIMM, VGA, iDP, Dual Intel® PCIe GbE, USB 3.2 Gen 1 (5Gb/s), SATA 6Gb/s, mSATA, HD Audio, Intel® AMT and RoHS.

Dual-channel DDR4 1600/2133 MHz 2 x SATA 6Gb/s 2 x RS-232/422/485



PCIe Mini slot provides mSATA and USB signal for full-size or half-size mSATA SSD and wireless LAN card.

USB Type

3G/Wi-Fi/USB devices

mSATA

» **PCI Express Backplane in PAC-400AI (HPE2-3S1)**

5-slot PICMG 1.3 backplane for half-size SBC, with one PCIe x16 Slot and one PCIe x4 Slot, RoHS.

