

TRUSTED BATTERY SOLUTIONS

















# PALP-14LHY 12.8V 48Wh CA 280A

Lithium Iron Phosphate (LiFePO4) Battery **Hyper Sport Pro Series** 

#### TERMINALS: (mm)




#### **DIMENSIONS: inch (mm)**



5.90 (150) 3.42 (87) W: 5.70 (145)

Tolerances are +/- 0.04 in. (+/- 1mm) and +/- 0.08 in. (+/- 2mm) for height dimensions. All data subject to change without notice.




#### **GLOBAL HEADOUARTERS** (USA AND INTERNATIONAL EXCLUDING EMEA)

**Power-Sonic Corporation** 

365 Cabela Dr Suite 300, Reno, Nevada 89523 USA

T: +1 619 661 2020

E: customer-service@power-sonic.com



### **POWER SONIC EMEA**

(EMEA - EUROPE, MIDDLE EAST AND AFRICA)

Smitspol 4, 3861 RS Nijkerk,

The Netherlands T NL: + 31 33 7410 700

TUK: +44 1268 560 686 TFR: +33 344 32 18 17

E: salesEMEA@power-sonic.com

# GO SMARTER

Active intelligent monitoring. At The heart of every Hyper Sport Pro Lithium battery is an integrated management system that monitors and reacts to multiple voltage, current, and temperature events to maximize performance, battery life and safety.

### GO SAFER

Lithium Iron Phosphate (LiFePO4) is the safest type of lithium battery and a ready to go replacement and upgrade from lead acid, AGM or gel.

#### GO FASTER

#### GO LONGER

- 4X lighter
- 4X longer life
- 4X faster charge time
- 4X the warranty

## GO HYPER SPORT PRO

Simply connect your battery and you are ready to go.

#### PERFORMANCE SPECIFICATIONS

I LIVI OKIMANOL SI LOH IDATIONS	
Nominal Voltage	12.8V
Watt-Hour	48
Discharge Continuous (40C) Maximum (70C, 15S)	160A 280A
Charging Current	2A (Standard) - 8A (Max)
Approximate Weight	2.42 lbs. (1.10 kg)
Initial Impedance	<12 milliohms
Cycle life (80% DOD at 77°F (25°C)	≥2000
Charge Retention (Shelf Life) (at 68°F /20°C) 1 Month	≥95%
Operating Temperature Range Charge Discharge Storage	32°F (0°C) to 113°F (45°C) -4°F (-20°C) to 131°F (55°C) -32°F (0°C) to 86°F (30°C)
Recommended Charger	Please contact Power Sonic
Case	230°C heat resistant case and cover UL94-V0 flammability
Upgrade to lead acid battery model	YTX14L-BS













**DISCHARGING CHART** 



Lithium Iron Phosphate (LiFePO4) Battery **Hyper Sport Pro Series** 





Transport Safety Certified

# 144 13.6 12.8 12.0

#### 1C-25C -30C -11.2 35C-10.4 40C -9.6 8.8 8.0 60 100 0 20 80 Capacity (%)

## **CHARGING**


The battery can be used if the voltage is higher or equal to 12.8V, although we recommend fully charging the battery if the voltage is below 13.0V. Apply constant voltage charge between 14.4V and 14.8V to fully charge the battery.

The Hyper Sport Pro series requires lithium compatible chargers and testers. We do not recommend the use of lead acid chargers as many in the market are not suitable for lithium iron phosphate batteries.

# APPLICATIONS

- Motorcycle
- ATV
- UTV

- Scooter
- Watersport



# WARRANTY

Designed and engineered at our ISO 9001:2001 certified factories all Power Sonic batteries are subject to stringent quality control through every step of the manufacturing process ensuring both consistency and reliability. The Hyper Sport series are backed by a 2-year limited warranty.

#### **GLOBAL HEADOUARTERS** (USA AND INTERNATIONAL EXCLUDING EMFA)

**Power-Sonic Corporation** 365 Cabela Dr Suite 300,

Reno, Nevada 89523 USA

T: +1 619 661 2020

E: customer-service@power-sonic.com

#### **POWER SONIC EMEA**

(EMEA - EUROPE, MIDDLE EAST AND AFRICA)

Smitspol 4, 3861 RS Nijkerk, The Netherlands

T NL: + 31 33 7410 700 TUK: +44 1268 560 686 TFR: +33 344 32 18 17

E: salesEMEA@power-sonic.com



#### **FURTHER INFORMATION**

Please refer to our website www.power-sonic.com for a complete range of useful tools and downloads, such as our PowerSports battery finder, application guides, material safety datasheets and much more.