



### Overview

Presentation	Factory assembled and tested Power Distribution Modules include circuit breaker, power cord, power connection, and circuit monitoring. Auto-detection of modules by the Modular PDU minimizes installation time.
Lead time	Usually Ships within 3 Weeks

### Main

Main Input Voltage	3 phase
Main Output Voltage	230 V
Provided Equipment	Installation guide

### Physical

Color	Gray
Height	5.98 in (15.2 cm)
Width	17.01 in (43.2 cm)
Depth	5.98 in (15.2 cm)
Net Weight	14.09 lb(US) (6.39 kg)

### Input

Input Frequency	50 Hz
Max line current	32 A

### Output

Maximum Total Current Draw per Phase	32 A
Number of power socket outlets	3 IEC 309 32 A 2P+E

### Conformance

Product Certifications	CE VDE
------------------------	-----------

### Ordering and shipping details

GTIN	731304257622
Package weight(Lbs)	16.09 lb(US) (7.3 kg)

### Packing Units

Package 1 Height	5.98 in (15.2 cm)
Package 1 width	17.01 in (43.2 cm)
Package 1 Length	5.98 in (15.2 cm)

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End Of Life Information</a>
Take-back	Take-back program available

## Contractual warranty

Warranty	1 year repair or replace
----------	--------------------------