



Overview

| | |
|--------------|--|
| Presentation | Factory assembled and tested Power Distribution Modules include circuit breaker, power cord, power connection, and circuit monitoring. Auto-detection of modules by the Modular PDU minimizes installation time. |
| Lead time | Usually Ships within 3 Weeks |

Main

| | |
|---------------------|--------------------|
| Main Input Voltage | 3 phase |
| Main Output Voltage | 120 V |
| Provided Equipment | Installation guide |

Physical

| | |
|------------|------------------------|
| Color | Black |
| Height | 5.00 in (12.7 cm) |
| Width | 17.52 in (44.5 cm) |
| Depth | 15.98 in (40.6 cm) |
| Net Weight | 12.24 lb(US) (5.55 kg) |

Input

| | |
|--------------------------|-------------|
| Input Frequency | 60 Hz |
| Acceptable Input Voltage | 200...240 V |
| Max line current | 30 A |

Output

| | |
|--------------------------------------|---------------|
| Maximum Total Current Draw per Phase | 30 A |
| Number of power socket outlets | 1 NEMA L21-30 |

Conformance

| | |
|------------------------|-----------|
| Product Certifications | UL Listed |
|------------------------|-----------|

Ordering and shipping details

| | |
|---------------------|------------------------|
| GTIN | 731304272465 |
| Package weight(Lbs) | 13.43 lb(US) (6.09 kg) |

Packing Units

| | |
|------------------|--------------------|
| Package 1 Height | 5.00 in (12.7 cm) |
| Package 1 width | 17.52 in (44.5 cm) |
| Package 1 Length | 15.98 in (40.6 cm) |

Offer Sustainability

| | |
|----------------------------|---|
| REACH Regulation | REACH Declaration |
| EU RoHS Directive | Under investigation |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | End Of Life Information |
| Take-back | Take-back program available |

Contractual warranty

| | |
|----------|--------------------------|
| Warranty | 1 year repair or replace |
|----------|--------------------------|