



## Overview

Lead time	Usually Ships within 3 Weeks
-----------	------------------------------

## Main

Main Input Voltage	3 phase
Provided Equipment	Installation guide

## Physical

Height	9.02 in (22.9 cm)
Width	17.99 in (45.7 cm)
Depth	27.99 in (71.1 cm)
Net Weight	52.01 lb(US) (23.59 kg)
Mounting Location	Front
Mounting preference	No preference
Mounting Mode	Not rack-mountable

## Input

Input Frequency	60 Hz
Number of input connectors	1 Hard Wire 5-wire (3PH + N + G)
Acceptable Input Voltage	200...240 V
Max line current	200 A
Load Capacity	72000 VA

## Output

Maximum Total Current Draw per Phase	200 A
--------------------------------------	-------

## Conformance

Product Certifications	UL Listed
------------------------	-----------

## Ordering and shipping details

GTIN	731304264521
Package weight(Lbs)	74.96 lb(US) (34 kg)

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Packing Units

Package 1 Height	15.98 in (40.6 cm)
Package 1 width	24.02 in (61 cm)
Package 1 Length	35.00 in (88.9 cm)

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Lead free	Yes

## Contractual warranty

Warranty	1 year repair or replace
----------	--------------------------