

QUARTZ-GOLD-5G

5G 2 x LAN, Single SIM, Low Latency Industrial Router



Key Features

- 5G/4G/3G industrial router
- Supports 5G SA/NSA ultra speed network
- MIPS Dual-core 880 MHz
- 256 Mb Flash
- 2 Gb DDR3 RAM
- 2 x Gigabit Ethernet ports
- Resilient against strong magnetic interference
- Metal enclosure for tough industrial applications
- VPN: PPTP/L2TP/L2TP V3/GRE/IPSec/Open VPN
- Optional Wi-Fi
- 1 x DC Power Interface (7.5 to 32 V DC)

3G UMTS	4G LTE	5G New Radio	AT Over IP	CLI Telnet	DATA Real-Time	Gbit Ethernet	IP Wireshark	LAN Dual Port	LIVE Stats
MIMO Antenna	PSU 7V to 32V	PTP Connect	RS232 Serial	SNMP Manage	SSH Manage	Syslog Service	TEMP -30 to +75C	UPNP Protocol	USER Portal
VLAN Network	VPN Tunnel	VRRP Protocol	WAN Backup	WEB Portal	WiFi 5 802.11ac	WiFi 2.4G & 5G	Win Linux/Mac	WW Global	

General Description


The QUARTZ-GOLD 5G is powered with a Mediatek 880 MHz MIPS dual-core processor with 256 Mb flash and 2 Gb of DDR3 RAM which drives the Linux based operating system.

A Quectel RM500QAE module is driven by the Qualcomm Snapdragon X55 5G Modem which provides the cellular capabilities of the QUARTZ-GOLD 5G and is manufactured on a leading edge 7 nm semiconductor fabrication process.

With Two Gigabit Ethernet interfaces, the QUARTZ-GOLD 5G also offers a RS232 interface that may be used to connect serial ports on products such as door access control panels and alarm panels to the Internet.

Wi-Fi is available as an option.

Gigabit WAN failover is supported to provide network redundancy for your connected gigabit LAN using the 5G NR or LTE Cat 4 cellular network.



QUARTZ-GOLD-5G

5G 2 x LAN, Single SIM, Low Latency Industrial Router

Additional Features

- » Supports DHCP server
- » Supports DNS proxy and Dynamic DNS (DDNS)
- » LED status lights
- » Supports 802.11 a/b/g/n/ac wireless standards (Option)
- » Supports captive portal
- » Local and remote management
- » SNMP network management, NTP support
- » LCP/ICMP/flow/heartbeat check

Cellular

- » 5G:
n1/n2/n3/n5/n7/n8/n12/n20/n25/n28/n38/
n40/n41/n66/n71/n77/n78/n79
- » LTE:
B1/B2/B3/B4/B5/B7/B8/B12/B13/B14/B17/
B18/B19/B20/B25/B26/B28/B29/B30/B32/
B34/B38/B39/B40/B41/B42/B43/B46/B48/
B66/B71
- » WCDMA:
B1/B2/B3/B4/B5/B6/B8/B19

Interfaces

- » 2 x GbE- configurable (1 x LAN, 1 x LAN/ 1 x WAN)
- » 1 x RS232 (based on 2 wire interface)
- » Wi-Fi: 802.11 a/b/g/n/ac (With Wi-Fi option)
- » 1 x SIM Slot
- » 4 x SMA (Female) 5G Antenna Interface
- » 2 x SMA-RP Wi-Fi (If equipped with Wi-Fi)

Environmental

- » Ruggedised industrial enclosure
- » Dimensions: 103 mm x 73.5 mm x 28 mm (with-out antenna)
- » Approx Weight: 320g (not including accessories and model dependent)
- » Operating Temperature Range: -30 to +75 °C
- » Storage Temperature Range: -40 to +85 °C
- » Relative Humidity: 0 - 95% Non-condensing

Router Settings

Network Protocols

- » IPv4
- » PPPoE
- » UDP/TCP/ICMP/NTP/DHCP
- » Modbus/TCP
- » HTTP/HTTPS
- » SNMP

Network Features

- » Cellular/WAN failover
- » VLAN
- » Bandwidth management
- » NAT/DMZ
- » IP passthrough/port redirection
- » Static/dynamic routing

VPN

- » PPTP/L2TP V3
- » GRE
- » IPSec
- » OpenVPN