

SPECIFICATION CONTROL DRAWING

10494

TITLE

COATED COPPER WIRE BRAID FOR SPECIAL DEVICES

DATE:

12-1-87

REVISION:

K

PART NUMBER:		PART NUMBER FOR SPECIAL DEVICES:		CONSTRUCTION
10494-1	-	D-096-16-01-00	-	8 carriers, 5 ends of AWG 38, Tin-Coated Copper, Gear: 12/39 Picks: 16.5 Braid Angle: 31.8
10494-2	-	D-096-16-02-00	-	16 carriers, 8 ends of AWG 36, Tin-Coated Copper, Gears: 35/30 Picks: 8.29 Braid Angle: 45.3
10494-3	-	D-096-16-03-00	-	24 carriers, 6 ends of AWG 36, Tin-Coated Copper, Gears: 30/30 Picks: 9.67 Braid Angle: 38.1
10494-4	-	D-096-16-04-00	-	24 carriers, 6 ends of AWG 36, Tin-Coated Copper, Gears: 36/30 Picks: 8.06 Braid Angle: 33.3
10494-5	-	D-096-16-05-00	-	16 carriers, 4 ends of AWG 36, Tin-Coated Copper, Gears: 30/30 Picks: 10.13 Braid Angle: 17.7
10494-6	-	D-096-22-01-00	-	16 carriers, 7 ends of AWG 36, Nickel-Coated Copper, Gears: 35/30 Picks: 8.29 Braid Angle: 14.4
10494-7	-	D-096-22-03-00	-	24 carriers, 6 ends of AWG 36, Nickel-Coated Copper, Gears: 36/30 Picks: 8.06 Braid Angle: 33.3
10494-8	-	D-096-16-06-00	-	24 carriers, 7 ends of AWG 36, Tin-Coated Copper, Gears: 43/30 Picks: 6.75 Braid Angle: 32.6
10494-9	-	D-096-22-02-00	-	24 carriers, 6 ends of AWG 36, Nickel-Coated Copper, Gears: 30/30 Picks: 9.67 Braid Angle: 38.1
10494-10	-	D-096-20-02-00	-	16 carriers, 8 ends of AWG 36, Silver-Coated Copper, Gears: 35/30 Picks: 8.29 Braid Angle: 45.3

DIMENSIONS ARE IN INCHES, AND UNLESS OTHERWISE DESIGNATED ARE NOMINAL.

Raychem

Raychem Corporation
300 Constitution Drive, Menlo Park, California 94025
415) 361 3333 TWX 910 373 1205

Page 1 of 2

THIS SPECIFICATION SHEET TAKES PRECEDENCE OVER DOCUMENTS REFERENCED HEREIN. REFERENCED DOCUMENTS SHALL BE OF THE ISSUE IN EFFECT ON DATE OF INVITATION FOR BID.

PART NUMBER:	PART NUMBER FOR SPECIAL DEVICES	CONSTRUCTION
10494-11	- D-096-22-04-00	- 8 carriers, 5 ends of AWG 38, Nickel-Coated Copper, Gears: 12/39 Picks: 16.5 Braid Angle: 31.8

(K)