



# RB751V-40-AU

## SURFACE MOUNT SCHOTTKY DIODES

Voltage    **40 V**

Current    **0.3 A**

### Features

- Extremely fast switching speed
- Surface mount package ideally suited for automatic insertion
- High conductor
- Lead free in compliance with EU RoHS 2.0
- Green molding compound as per IEC 61249 standard
- AEC-Q101 qualified

### Mechanical Data

- Case: SOD-323 Package
- Terminals: Solderable per MIL-STD-750, Method 2026
- Approx. Weight: 0.00014 ounces, 0.0041 grams

**SOD-323**



### Maximum Ratings and Thermal Characteristics ( $T_A = 25^\circ\text{C}$ unless otherwise noted)

PARAMETER	SYMBOL	LIMIT	UNITS
Maximum Repetitive Peak Reverse Voltage	$V_{RRM}$	40	V
Maximum Rms Voltage	$V_{RMS}$	28	V
Maximum Dc Blocking Voltage	$V_{DC}$	40	V
Maximum Average Forward Current	$I_{F(AV)}$	0.3	A
Peak Forward Surge Current : 1 s Single Half Sine-Wave Superimposed On Rated Load	$I_{FSM}$	0.6	A
Maximum Junction Capacitance Measured at 1 MHZ And Applied $V_R = 0 \text{ V}$	$C_J$	5	pF
Typical Thermal Resistance	$R_{\theta JA}^{(1)}$	650	$^\circ\text{C}/\text{W}$
Operating Junction Temperature Range	$T_J$	-55~150	$^\circ\text{C}$
Storage Temperature Range	$T_{STG}$	-55~150	$^\circ\text{C}$



## RB751V-40-AU

**Electrical Characteristics** ( $T_A = 25^\circ C$  unless otherwise noted)

PARAMETER	SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNITS
Forward Voltage	$V_F$	$I_F = 1 \text{ mA}, T_J = 25^\circ C$	-	-	0.37	V
		$I_F = 1 \text{ mA}, T_J = 125^\circ C$	-	0.21	-	
		$I_F = 10 \text{ mA}, T_J = 125^\circ C$	-	0.35	-	
		$I_F = 40 \text{ mA}, T_J = 125^\circ C$	-	0.55	-	
Reverse Current	$I_R^{(2)}$	$V_R = 30 \text{ V}, T_J = 25^\circ C$	-	-	0.5	uA
		$V_R = 40 \text{ V}, T_J = 25^\circ C$	-	-	1	
		$V_R = 40 \text{ V}, T_J = 125^\circ C$	-	22	-	

NOTES:

1. Mounted on a FR4 PCB, single-sided copper, mini pad.
2. Short duration pulse test used to minimize self-heating effect



# RB751V-40-AU

## TYPICAL CHARACTERISTIC CURVES




Fig.1 Forward Current Derating Curve




Fig.2 Typical Junction Capacitance




Fig.3 Typical Reverse Characteristics




Fig.4 Typical Forward Characteristics




Fig.5 Operating Temperature Derating Curve



## RB751V-40-AU

### Part No Packing Code Version

Part No Packing Code	Package Type	Packing Type	Marking	Version
RB751V-40-AU_R1_000A1	SOD-323	5K / 7" Reel	P60	Halogen free

### Packaging Information & Mounting Pad Layout

