



RCX3M-Z

3 pole male XLR cable connector with IP65 dust-water proof design.





Features and benefits

- IP65 rating provides outdoor protection under mated condition
- UL94 V-0 rated materials

• Chrome&Black plated with fashionable finish and better abrasion performance



Article Variations

Article Name	Details	Packaging
RCX3M-Z-000-0/1	Chrome plated housing, tin plated contacts	BULK / Plastic Bag
RCX3M-Z-001-0/1	Black plated housing, tin plated contacts	BULK / Plastic Bag
RCX3M-Z-002-0/1	Black plated housing, gold plated contacts	BULK / Plastic Bag



Technical Information

Product	
Title	RCX3M-Z
Connection Type	XLR
Gender	male

Electrical		
Contact resistance	\leq 5 m Ω	
Dielectric strength	1,5 kVdc	
Insulation resistance	> 10 G Ω (initial)	
Rated current per contact	16 A	
Rated voltage	< 50 V	

Mechanical		
Cable O.D.	5.0 - 8.0 mm	
Insertion force	≤ 60 N	
Withdrawal force	≤ 60 N	
Lifetime	> 1000 cycles	
Wiresize	Max. 1.5 mm2	
Wiresize	Max. 16 AWG	
Wiring	Solder contacts	
Locking device	Latch lock	