



RCX5F-Z

5 pole female XLR cable connector with IP65 protection





Features & Benefits

- IP65 rating provides outdoor protection under mated condition
- UL94 V-0 rated materials

 Chrome & Black plated with fashionable finish and better abrasion performance



Article Variations

Article Name	Details	Packaging
RCX5F-Z-000-0/1	Chrome plated housing, tin plated contacts	BULK / Plastic Bag
RCX5F-Z-001-0/1	Black plated housing, tin plated contacts	BULK / Plastic Bag
RCX5F-Z-002-0/1	Black plated housing, gold plated contacts	BULK / Plastic Bag



Technical Information

Product	
Title	RCX5F-Z
Connection Type	XLR
Gender	female

Electrical		
Contact resistance	≤ 5 mΩ	
Dielectric strength	1,5 kVdc	
Insulation resistance	> 10 GΩ (Initial)	
Rated current per contact	7.5 A	
Rated voltage	< 50 V	

Mechanical		
Cable O.D.	5.0 - 8.0 mm	
Insertion force	≤60 N	
Withdrawal force	≤60 N	
Lifetime	> 1000 cycles	
Wiresize	Max 1.0 mm2	
Wiresize	Max 18 AWG	
Wiring	Solder contacts	
Locking device	Latch lock	