

## ReliaGATE 15-10

- General purpose M2M and IoT gateway, meeting high-reliability operational requirements
- Low power, allowing long battery life and minimizing power requirements
- Device management, Over-The-Air configurable, secure remote access and application lifecycle management
- Flexible, offering multiple wired and wireless connectivity



### FEATURES

**Industrial** – Meets the needs of demanding environments through temperature operation, shock and vibration certification, and transient and isolation protection

**Programmable** – Provided with open standard Yocto Linux operating system, enabled with Eurotech's Everyware Software Framework (ESF) and its plug-ins, simplifying the creation of applications utilizing Java on an Eclipse IDE

**Ready-to-Deploy, Carrier Certified** – Change which pre-certified Eurotech ReliaCELL 10-20 modular cellular adapter is installed, and the ReliaGATE 15-10 is immediately deployable on different mobile carrier networks, based on geography, preference and coverage

**Seamless Integration** – Builds upon integrated Quark processor hardware and software building blocks offering in Intel® Gateway Solutions for the Internet of Things (IoT), with Everyware Software Framework (ESF) support to extend capabilities further, including remote device management and Java programmability

**M2M and IoT (Internet of Things) Building Block** – Connects sensors, actuators and devices to business systems in the industrial and automation arena to enable M2M and IoT services and applications. Natively integrated to the Eurotech Everyware Cloud M2M Integration Platform for fast service development and deployment

The ReliaGATE 15-10 is a flexible Multi-Service Gateway serving a broad range of applications and specifically designed for M2M and IoT solutions. It offers companies a rugged and reliable gateway and edge controller for data aggregation, on-board processing, and data transfer to simplify industrial operations, including functions such as inventory control, facilities management, assembly line oversight, and asset monitoring. The ReliaGATE operates at extended temperature range, with industrial-grade connectors, multiple I/O capabilities and wired or wireless connectivity for automation and industrial applications.

Using the low power Intel® Quark SoC processor, the ReliaGATE 15-10 performs advanced computational functions even under battery power. Low power draw means longer runtimes for the ReliaGATE 15-10 with reduced heat generation to minimize impact on the surrounding environment and control operational costs. ReliaGATE 15-10 offers benefits through the integration of the hardware, drivers, operating system and Eurotech's Everyware Software Framework (ESF) device-resident application development framework to shorten time to market for products and service offerings.

The ReliaGATE 15-10 offers control and configuration options. A web interface allows easy configuration and application management of individual units. Another option allows individual or multiple units to be managed, configured, updated or rolled back through the Remote Device Management function of the Everyware Device Cloud full M2M solution from Eurotech. Both options, either with the Everyware Cloud service or independent of it, make the ReliaGATE 15-10 fast to deploy and upgrade over time.

### System Architecture



ReliaGATE 15-10 is shown with ReliaCELL 10-20 ruggedized cellular adapter. For more info please visit our website [www.eurotech.com](http://www.eurotech.com)



CPU	Intel® Quark SoC X1020D, 400Mhz
MEMORY	MicroSD Slot (4GB up to 64GB) 512MB DDR3 (support to 1GB)
WIRELESS	<b>GPS</b> – Supported with ReliaCELL (internal discrete GPS soldered down optional) <b>WIFI</b> – 802.11 a/b/g/n/- Access Point & Client <b>CELLULAR</b> – Supported with ReliaCELL up to 150mbps
INTERFACE	<b>USB</b> 3x USB 2.0 ports (1x USB 2.0 used for ReliaCELL) <b>ETHERNET</b> 2x 100Mbit LAN Ethernet ports <b>SERIAL</b> 1x RS232/RS485/RS422 (option for 2x RS232) 1x RS232/TTL (General purpose or Console port) <b>GPIO</b> 3x, 3.3V levels, protected to IEC61000 (15kv) <b>CAN</b> 1x CANBus High Speed port. 2.0B, up to 1Mbit/s HS port 1x CANBus Low Speed port 2.0B, up to 250kbit/s LS port <b>AUDIO</b> 1x Channel line out 1x Mic input (optional voice via modem and I/O mixing) <b>INPUTS</b> 3x Analog input 0-36V, 10bit
ROUTING	Static Routes DHCP DNS Client Firewalling SECURITY AES, 3DES, SSH, IPsec NAT (Network Address Translation) Port Forwarding
POWER SUPPLY	6.5 to 36 VDC (Nominal 12) with transient protection Vehicle ignition input Low power mode of operation Optional back-up battery with integrated battery charger and monitoring
POWER CONSUMPTION	8W Typical
OS SUPPORT	Yocto Linux
INTEL GATEWAY SOLUTIONS FOR IOT READY	Yes
ESF READY	Yes
EDC READY	Yes
DIMENSIONS	5.4" x 3.8" x 1.7"/ 137 x 97 x 43 mm (L x W x H)
OPERATING TEMPERATURE	Industrial temperature: -40° to +80°C
STORAGE TEMPERATURE	-40° to +85°C
HUMIDITY	95% relative humidity at +45°C non-condensing
COMPLIANCE	CE, FCC, IC, J1455, UL Equivalent



Note: The information in this document is subject to change without notice and should not be construed as a commitment by EUROTECH. While reasonable precautions have been taken, EUROTECH assumes no responsibility for any error that may appear in this document. All trademarks or registered trademarks are the properties of their respective companies.