



Mono 1/4" right-angle plug









Article Variations

Article Name	Details	Packaging
RP2RC	Nickel plated housing, nickel plated contacts	Plastic Packaging
RP2RC-D	Nickel plated housing, nickel plated contacts	BULK
RP2RC-B	Black plated housing, gold plated contacts	Plastic Packaging
RP2RC-B-D	Black plated housing, gold plated contacts	BULK
RP2RC-BAG	Black plated housing, nickel plated contacts	Plastic Packaging
RP2RC-BAG-D	Black plated housing, nickel plated contacts	BULK



Product	
Title	RP2RC
Connection Type	Plug

Electrical		
Contact rated current	depends on mating connector $m\Omega$	
Contact resistance	depends on mating connector $m\Omega$	
Dielectric strength	1 kV dc	
Insulation resistance	> 1.5 GΩ	

Mechanical		
Lifetime	> 1000 mating cycles	
Cable O.D.	4 - 7 mm	
Wiresize	1.0 mm²	
Wiresize	18 AWG	
Wiring	Solder contacts	

Material		
Boot	PA6+30% GF	
Contact	Brass (CuZn39Pb3)	
Contact plating	Nickel / Au	
Shell	Zinc alloy	
Shell plating	Nickel / Black	
Strain relief	POM	