

RRC2037

Standard Battery Pack Li-Ion

7.20V / 2.90Ah / 20.90Wh

P/N: 110133



Picture only for reference



Features

- Worldwide approvals and certification of safety standards
- No development costs, fast time-to-market
- Smart batteries with numerous features according to the SMBus specification
- Integrated LED State of Charge (SoC) indicator
- State-of-the-art lithium-ion cells with the market’s highest energy density
- High discharge performance
- JEITA charging profile optimization
- Numerous and redundant safety features, e.g.:
 - CUV (Cell Under Voltage): protection against deep discharge
 - COV (Cell Over Voltage): protection against over charge
 - OTC (Over Temperature in Charge): protection against overheating while charging
 - OTD (Over Temperature in Discharge): protection against overheating during discharging
 - Battery Life Management: protection against rapid cell ageing
- Increased ESD protection up to 8.00kV
- SHA-1 cryptosystem to prevent plagiarism
- Life expectancy: Up to 80% of initial capacity after 800 cycles

Applications

Suitable for use with industrial and medical devices, etc.

Specification

General

Delivery status battery capacity	<30%
Compliance information	IEC 62133 / CE / UL2054 / FCC / UKCA / PSE / KC / BSMI / Gost / CMIM / CQC / RCM / BIS / UN 38.3 / RoHS / REACH
Operating temperature	0°C to 45°C (charge) -20°C to 60°C (discharge)
Storage temperature	-20°C to 50°C max. -20°C to 25°C recommended

Electrical Parameters

Nominal voltage	7.20V
Nominal capacity	2.90Ah
Initial impedance	<200mΩ @ 1kHz at 25°C
Max. charge current	2.03A
Max. charge voltage	8.40V
Max. discharge current	4.50A


Battery Dimensions

Length	85.39mm +0.40/-0.40
Width	41.99mm +0.40/-0.40
Thickness	22.40mm +0.40/-0.25
Weight	121g
Contacts	+, C, D, T, -
Ingress protection	IP40

Safety Parameters PCM

Overcharge detection voltage / cell	4.25V
Overdischarge detection voltage / cell	2.50V
Overcharge detection current	2.75A
Overdischarge detection current	4.80A

Recommended Accessories

Type	Product	P/N	Application
Standard Battery Charger	 RRC-SMB-UBC RRC-SMB-UBC-M	100485 110105	60.00W standard battery charger for optimized charging process. With external power supply for worldwide use.
Standard Battery Charger	 RRC-SMB-MBC RRC-SMB-MBC-M	110017 110104	50.00W standard battery charger for optimized charging process. With external power supply for worldwide use.
Standard Battery Charger	 RRC-SMB-DBC	110111	Dual bay standard battery charger for optimized charging process. With external power supply for worldwide use.
Power Management Module	 RRC-PMM240	100576	Power management module for smart battery charging with automatic power source selection. Fits to all RRC20xx standard smart batteries.
Power Supply AC/DC	 PS65	210919	External power supply (worldwide use) for embedded battery charger RRC-PMM240 or for mobile devices. Included in RRC-SMB-UBC/MBC.
3-pol AC-Cable	 US-Version EU-Version UK-Version AU-Version	210950 210951 211133 211134	Country specific power cable for PS65.
Car Adapter DC/DC	 RRC-SMB-CAR	110041	90.00W car adapter with USB charging port. Power supplying in cars and trucks for RRC-SMB-UBC, RRC-SMB-MBC, RRC-PMM240 or mobile devices.