
# ELECTRIC DOUBLE LAYER CAPACITORS "DYNACAP"



# 5.5V Low Profile and High Temperature Capacitors



- High temperature type of series DB.
- Small-sized, large capacity, excellent voltage holding.
- For all ratings, uniform 5mm pitch of terminal spacing.
- $\phi$ 13.5×7.5L size can encase up to 0.33F.
- Ideal for backing up of CMOS's, IC's, microcomputers, RAM's, RTC's and the like used in Video's, tuners, TV sets, telephone sets and others.






Marking color: White print on a black sleeve

#### Specifications

Item	Performance						
Category temperature range (°C)	-10 to +85						
Tolerance at rated capacitance (%)	%) -20 to +80						
Internal resistance	Rated capacitance (F) 0.047 0.1	0.22	0.33	0.47	1	]	
at 1 kHz	Internal resistance (Ω Max.) 200 150	150	150	100	75	]	
Characteristics at high and low temperature		Within ±30% of the value at 20°C  Less than four times of the initial specified value.					
Endurance (85°C)	Percentage of capacitance change Within ±3	1000 hours  Within ±30% of the initial measured value  Less than four times of the initial specified value					
Shelf life (85°C)	Test time: 1000 hours; Same as endurance.						
Applicable standards	Conforms to JIS C5160-1 2009 (IEC 62391-1 2006)						

## **Outline Drawing**



Part numberin	rt numbering system (example : 5.5V0.1F)					
DBJ	_	5R5	D	104	Т	
Series code	Max.operating voltage symbol Rated capacital symbol		Rated capacitance symbol			

Part number is refer to following table.

### Standard Ratings

_			
Max. operating voltage (V)	Rated capacitance (F)	ELNA Parts No.	φD×L (mm)
5.5	0.047	DBJ-5R5D473T	13.5×7.5
5.5	0.1	DBJ-5R5D104T	13.5×7.5
5.5	0.22	DBJ-5R5D224T	13.5×7.5
5.5	0.33	DBJ-5R5D334T	13.5×7.5
5.5	0.47	DBJ-5R5D474T	21.5×8.0
5.5	1	DBJ-5R5D105T	21.5×8.0