

S3100-4040

Media Converters

Stand-alone Fiber to Fiber Media Converter SFP to SFP for Data Rates from 100Mbps to 2.5Gbps

The ION S3100 is a stand-alone fiber to fiber media converter. It is protocol independent and supports data rates from 100Mbps to 2.5Gbps through two open SFP slots. This any-rate to same-rate converter can be used to perform reliable and cost-effective single mode to multimode fiber conversion or it can be used to provide wavelength conversion in CWDM applications.



Key Features

- Protocol Transparent
- Supports data rates from 100Mbps to 2.5Gbps
- · Any-rate to same-rate conversion
- SFP to SFP Fiber Repeater
- · Specific wavelength CWDM Transponder
- Supported protocols: Fast Ethernet, Gigabit Ethernet, SONET (OC-3/12/48), 1 & 2 Gig Fiber Channel, 2.5G InfiniBand, FDDI, ESCON/ SBCON
- · Link Pass Through
- Automatic Link Restoration

Specifications

Standards Multi-Source Agreement (MSA)

	Small Form Factor Pluggable (SFP)
Data Rates	Protocol Independent 100Mbps to 2.5Gbps
Max Frame Size	16384 bytes Jumbo Frames Supported
Status LEDs	PWR: ON (Green) = Power Port 1 Link: ON = Fiber Signal Detected Port 2 Link: ON = Fiber Signal Detected
Dimensions	Width: 3.25" [82 mm] Depth: 6.5" [165 mm] Height: 1" [25 mm]
Power Consumption	2-3 Watts (based on the SFP modules used)
Power Supply	External AC/DC required: 12VDC Output; 120-240VAC input
Environment	Operating: 0°C to 50°C Storage: -40°C to 85°C Humidity: 5% to 95% (non-condensing) Altitude: 0 – 10,000 ft.
Weight	2 lbs. [0.90 kg]
MTBF	Greater than 250,000 hours (MIL-HDBK- 217F) Greater than 687,000 hours (Bellcore)
Certifications	FCC Class A, EN55022 Class A, EN55024, CE Mark
Warranty	Lifetime

Power Supply Included

To order the corresponding country specific power supply, add the extension from the list below to the end of the SKU; Ex: S3100-4040-**NA**

-NA = Country Code

-NA = North America -LA = Latin America -EU = Europe -UK = United Kingdom -SA = South Africa -JP = Japan -OZ = Australia -BR = Brazil

Ordering Information

3100-4040

100Mbps to 2.5Gbps fiber repeater with two open SFP slots, any-rate to same-rate stand-alone media converter

Optional Accessories (sold separately)

SFP Modules

SFP and SFP+ modules supported

Mounting Options (sold separately)

WMBL

Wall Mount Bracket 4" [102 mm]

VMBD DIN Rail Bracket 5" [127 mm]

4-Slot Media Converter Shelf