



**865-870 MHz 5.5 dBi CP MINI RFID PANEL ANTENNA**

The Laird S8655P is a high-performance RFID antenna lineup and is the only UHF RFID antenna available to the market that offers no-compromise performance in a small package. At only 5.2" square the antenna offers a gain specification of 5.0 dBi and axial ratio better than 2 dB. In effect the antenna is providing the performance one would expect of a much larger antenna. The antenna is not only mechanically robust but is less likely to be exposed to excessive damage by virtue of its reduced size.

**FEATURES** 


- Low profile
- Extremely low VSWR and axial ratio
- IP 67 Rated
- Weather and UV resistant radome
- Wide range of connector options
- Left hand and right hand CP versions

**APPLICATIONS**

- Warehouse
- Distribution center
- Airports and hospitals
- Transit terminals
- Conveyor belt

**SPECIFICATIONS**

Antenna Part Number	S8655PR and S8655PL
Frequency Range	865 - 870 MHz
Gain	5.0 dBi
Maxium VSWR	1.5:1
3 dB Beamwidth - Azimuth	100°
Front to Back Ratio	8 dB
Polarization	Circular RH or Circular LH
Maxium Input Power	10 Watts
Input Impedence	50 Ohms
Axial Ratio	2.0 dB Typical
Weight lb. (Kg)	1.0 lbs (.45)
Mechanical Size in. (mm)	5.2" x 5.2" x .71" (132.1 x 132.1 x 17.8)
Antenna vConnection	Type N Female, RP-TNC Female, RP-SMA Female, SMA Female
Radome	White or Charcoal High Strengh PC
Mount Style	Threaded Stud 2x #10-32
Temperature Operational	-30°C to +70°C
Storage Temperature	40°C to 85°C
Impact Resistance	1 lbs. Ball Drop, 24"
Salt	MIL-STD-810
Vibration	MIL-STD-810
Shock	IEC 68-2-27
Humidity	IEC 68-2-30
Lightning Protection	DC Grounded
Enclosure Rating	IP 67



Americas: +1.847.839.6925  
IAS-AmericasEastSales@lairdtech.com

Europe: +44.1628.858941  
IAS-EUSales@lairdtech.com

Asia: IAS-AsiaSales@lairdtech.com

[www.lairdtech.com](http://www.lairdtech.com)

**ANT-DS S8655P 1115**

Any information furnished by Laird Inc. and its agents is believed to be accurate and reliable. All specifications are subject to change without notice. Responsibility for the use and application of Laird materials rests with the end user, since Laird and its agents cannot be aware of all potential uses. Laird makes no warranties as to the fitness, merchantability or suitability of any Laird materials or products for any specific or general uses. Laird shall not be liable for incidental or consequential damages of any kind. All Laird products are sold pursuant to the Laird Terms and Conditions of sale in effect from time to time, a copy of which will be furnished upon request. © Copyright 2015 Laird Inc. All Rights Reserved. Laird, Laird Technologies, the Laird Logo, and other marks are trademarks or registered trademarks of Laird Inc. or an affiliate company thereof. Other product or service names may be the property of third parties. Nothing herein provides a license under any Laird or any third party intellectual property rights.