

## 1700V/10A Silicon Carbide Power Schottky Barrier Diode

### Features

- Rated to 1700V at 10 Amps
- Zero reverse recovery current
- Zero forward recovery voltage
- Temperature independent switching behavior
- High temperature operation
- High frequency operation


### Benefits

- Unipolar rectifier
- Substantially reduced switching losses
- No thermal run-away with parallel devices
- Reduced heat sink requirements

### Applications

- SMPS, e.g., CCM PFC;
- Motor drives, Solar application, UPS,  
Wind turbine, Rail traction, EV/HEV

Key Characteristics		
$V_{RRM}$	1700	V
$I_F, T_c \leq 135^\circ\text{C}$	17	A
$Q_c$	122	nC



Part No.	Package Type	Marking
<b>SC2S17010A</b>	TO-220-2 pin	<b>SC17010</b>

## Maximum Ratings

Parameter	Symbol	Test Condition	Value	Unit
Repetitive Peak Reverse Voltage	V <sub>RRM</sub>		1700	V
Surge Peak Reverse Voltage	V <sub>RSM</sub>		1700	V
DC Blocking Voltage	V <sub>DC</sub>		1700	V
Continuous Forward Current	I <sub>F</sub>	T <sub>C</sub> =25°C T <sub>C</sub> =135°C T <sub>C</sub> =156°C	35 17 10	A
Repetitive Peak Forward Surge Current	I <sub>FRM</sub>	T <sub>C</sub> =25°C, tp=10ms, Half Sine Wave, D=0.3	50	A
Non-repetitive Peak Forward Surge Current	I <sub>FSM</sub>	T <sub>C</sub> =25°C, tp=10ms, Half Sine Wave	90	A
Power Dissipation	P <sub>TOT</sub>	T <sub>C</sub> =25°C T <sub>C</sub> =110°C	192 82	W
Operating Junction	T <sub>j</sub>		-55°C to 175°C	°C
Storage Temperature	T <sub>stg</sub>		-55°C to 175°C	°C
Mounting Torque		M3 Screw 6-32 Screw	1 8.8	Nm lbf-in

## Thermal Characteristics


Parameter	Symbol	Test Condition	Value	Unit
			Typ.	
Thermal resistance from junction to case	R <sub>th JC</sub>		0.78	°C/W

## Electrical Characteristics


Parameter	Symbol	Test Conditions	Numerical		Unit
			Typ.	Max.	
Forward Voltage	V <sub>F</sub>	I <sub>F</sub> =10A, T <sub>j</sub> =25°C	1.4	1.7	V
		I <sub>F</sub> =10A, T <sub>j</sub> =175°C	2.1	3	
Reverse Current	I <sub>R</sub>	V <sub>R</sub> =1700V, T <sub>j</sub> =25°C	30	100	μA
		V <sub>R</sub> =1700V, T <sub>j</sub> =175°C	50	200	
Total Capacitive Charge	Q <sub>C</sub>	V <sub>R</sub> =1200V, T <sub>j</sub> =150°C $Q_C = \int_0^{V_R} C(V)dV$	122	-	nC
Total Capacitance	C	V <sub>R</sub> =0V, T <sub>j</sub> =25°C, f=1MHZ	1400	1600	pF
		V <sub>R</sub> =400V, T <sub>j</sub> =25°C, f=1MHZ	90	120	
		V <sub>R</sub> =800V, T <sub>j</sub> =25°C, f=1MHZ	66	80	

## RATING AND CHARACTERISTICS CURVES (SC2S17010A)


1) Forward IV characteristics as a function of  $T_j$  :




2) Reverse IV characteristics as a function of  $T_j$  :




3) Current Derating



4) Capacitance vs. reverse voltage :



## Package TO-220



DIM	Millimeters		Inches	
	Min.	Max.	Min.	Max.
A	4.4	4.6	0.173	0.181
C	1.23	1.32	0.048	0.052
D	2.4	2.72	0.094	0.107
E	0.49	0.7	0.019	0.028
F	0.61	0.88	0.024	0.035
F1	1.14	1.7	0.045	0.067
F3		1		0.039
G	4.95	5.15	0.195	0.203
H1	7.7	7.9	0.303	0.311
H2	10	10.4	0.394	0.409
L2		16.4		0.646
L3		28.9		1.138
L4	13	14	0.512	0.551
L5	2.65	2.95	0.104	0.116
L6	15.25	15.75	0.6	0.62
L7	6.2	6.6	0.244	0.26
L9	3.5	3.93	0.138	0.155
M		2.6		
V		5°		
V2		30°		
V4		45°		
diam	3.75	3.85	0.148	0.152