



**Mallory Sonalert Products, Inc.**

Part #:

**SCE028XD2MG7B**

# Sales Outline Drawing

Revision:

**D**

## Specifications:

|                        |                                                                                            |                            |  |  |
|------------------------|--------------------------------------------------------------------------------------------|----------------------------|--|--|
| Sound Level Category:  | Extra Loud                                                                                 | Loud                       |  |  |
| Mode of Operation:     | Continuous                                                                                 | Ding Dong 2.0 - 1.6 kHz    |  |  |
| Pulse Rate (PPS):      | N/A                                                                                        | 1.2                        |  |  |
| Loudness @ 2 FT:       | 95 to 105 dB(A) Typ.                                                                       | 85 to 95 dB(A) Typ.        |  |  |
| Frequency:             | 2000 ± 500 Hz                                                                              | 2000 ± 500 Hz              |  |  |
| Connection:            | T-BLOCK ONLY                                                                               | T-BLOCK; BLACK WIRE TO (-) |  |  |
| Voltage Rating:        | 16 to 28 VDC                                                                               |                            |  |  |
| Current Draw:          | 40mA MAX                                                                                   |                            |  |  |
| Housing Material:      | 6/6 Nylon, Color: Black                                                                    |                            |  |  |
| Storage Temperature:   | -40° to +85° C                                                                             |                            |  |  |
| Operating Temperature: | -40° to +85° C                                                                             |                            |  |  |
| Panel Mounting:        | Recommended hole size is 1.25"(31.75mm). Thread front will fit standard 30mm(1.181") hole. |                            |  |  |
| Knurled Nut:           | Used to attach part to panel. The max recommended torque is 10 in-lbs.                     |                            |  |  |
| Weight (Typical):      | 2.1 oz (60g)                                                                               |                            |  |  |
| NEMA 3R,4X, & 12:      | Approved with use of ACC03.                                                                |                            |  |  |
| cUL Recognition:       | cUL Recognized                                                                             |                            |  |  |
| Options:               | Please contact factory.                                                                    |                            |  |  |

## Dimensions: Inches (mm)

**ROHS Compliant**

