



**Mallory Sonalert Products, Inc.**

Part #:

**SCE028XD3MG4B**

# Sales Outline Drawing

Revision:

**C**

## Specifications:

|                        |  |                            |                             |                            |
|------------------------|--|----------------------------|-----------------------------|----------------------------|
| Sound Level Category:  | Extra Loud   | Extra Loud                 | Extra Loud                  | Loud                       |
| Mode of Operation:     | Continuous   | Double Pulse               | Quick Pulse                 | Dual Tone                  |
| Loudness @ 2 FT:       | 95 to 105 dB(A) Typ.   | 95 to 105 dB(A) Typ.       | 95 to 105 dB(A) Typ.        | 85 to 95 dB(A) Typ.        |
| Pulse Rate (PPS):      | N/A  | 2                          | 60                          | 1.5                        |
| Frequency:             | 2900 ± 500 Hz  | 2900 ± 500 Hz              | 2900 ± 500 Hz               | 3.0 - 2.9 kHz              |
| Connection:            | T-BLOCK ONLY   | T-BLOCK; BLACK WIRE TO (-) | T-BLOCK; YELLOW WIRE TO (-) | T-BLOCK; BOTH WIRES TO (-) |
| Voltage Rating:        | 16 to 28 VDC   |                            |                             |                            |
| Current Draw:          | 40mA MAX   |                            |                             |                            |
| Housing Material:      | 6/6 Nylon, Color: Black  |                            |                             |                            |
| Storage Temperature:   | -40° to +85° C   |                            |                             |                            |
| Operating Temperature: | -40° to +85° C   |                            |                             |                            |
| Panel Mounting:        | Recommended hole size is 1.25"(31.75mm). Thread front will fit standard 30mm(1.181") hole. |                            |                             |                            |
| Knurled Nut:           | Used to attach part to panel. The max recommended torque is 10 in-lbs.                     |                            |                             |                            |
| Weight (Typical):      | 1.6 oz (45g)   |                            |                             |                            |
| NEMA 3R,4X, & 12:      | Approved with use of ACC03.  |                            |                             |                            |
| cUL Recognition:       | cUL Recognized   |                            |                             |                            |
| Options:               | Please contact factory.  |                            |                             |                            |

**Dimensions:** Inches (mm)

**cUL Recognized**

**ROHS Compliant**

