







# SOCKETS

| SOCKETS  |  |   |
|--|--|---|
| Product  | Features   | Accessory For   |
| <p><b>OT08PC</b><br/>Octal Socket 8-Pin</p>   | <p>8-pin 35mm DIN rail or surface mount octal socket. Rated at 10A @ 600VAC and has pressure clamp terminals.</p>  | <p><b>AWG 12 to 22 (3.2 to 0.33 mm<sup>2</sup>) wire sizes. Consult individual datasheet for compatibility</b></p>  |
| <p><b>NDS-8</b><br/>Octal Socket 8-Pin<br/>Screw terminals with captive wire clamps</p>       | <p>8-pin 35mm DIN rail or surface mount octal socket. Rated at 10A @ 300VAC. Surface mounted with two #6 (M 3.5 x 0.6) screws or snaps onto a 35 mm DIN rail. A spring mechanism allows easy removal. Uses PSC8 hold-down clips.</p> | <p><b>Up to two #14 AWG (2.45 mm<sup>2</sup>) wire size</b><br/><b>Series:</b><br/> <b>ARP FS500 LLC4 LLC5</b><br/> <b>PRLM TDB TDBH TDBL</b><br/> <b>TDI TDIH TDIL TDM</b><br/> <b>TDMB TDMH TDML TDR</b><br/> <b>TDS TDSH TDSL TRDU</b><br/> <b>TRM TRS TRU</b></p> |
| <p><b>P1011-6</b><br/>Octal Socket 8-Pin</p>    | <p>8-pin surface mount socket with binder head screw terminals. Rated at 10A @ 600VAC. UL Listed combination when used with TDM, TDB, TDS Series timers. Uses PSCRB8 hold-down brackets.</p>   | <p><b>Series:</b><br/> <b>ARP FS500 LLC4 LLC5</b><br/> <b>PRLM TDB TDM TDMB</b><br/> <b>TDR TDS TRB TRDU</b><br/> <b>TRM TRS TRU</b></p>  |
| <p><b>OT11PC</b><br/>Magnal Socket 11-Pin</p>   | <p>Magnal Sockets are for plug-in units</p>  | <p><b>11-pin Plug-in units</b><br/><b>Series:</b><br/> <b>ARP LLC6 TDB TDBH</b><br/> <b>TDBL TDMB TDS TDSH</b><br/> <b>TDSL TRB TRDU TRM</b><br/> <b>TRS TRU</b></p>  |
| <p><b>SD12-PC</b><br/>Rectangle Socket 12-pin</p>   | <p>12-pin surface Rectangle Socket.</p>  | <p><b>ACBC-120</b></p>  |
| <p><b>NDS-11</b><br/>11-pin Magnal Socket<br/>Screw terminals with captive wire clamps</p>  | <p>11 pin 35 mm DIN rail or surface mount socket. Rated at 10A @ 300VAC. Surface mounted with two #6 (M 3.5 x 0.6) screws or snaps onto a 35 mm DIN rail. A spring mechanism allows easy removal. Uses PSC11 hold-down clips.</p>    | <p><b>AWG 12 to 22 (3.2 to 0.33 mm<sup>2</sup>) wire sizes</b><br/><b>Series:</b><br/> <b>ARP LLC6 TDB TDBH</b><br/> <b>TDBL TDMB TDS TDSH</b><br/> <b>TDSL TRB TRDU TRM</b><br/> <b>TRS TRU</b></p>  |