

ELECTRET CONDENSER MICROPHONE


MEO-94P-01-Series

Omnidirectional & RoHS Compliant


SPECIFICATIONS:

TYPE	MEO-94PD-01-Series MEO-94PN-01-Series
FREQUENCY RESPONSE (Hz)	20 ~ 16,000 Hz.
DIRECTIVITY	Omnidirectional
SENSITIVITY ($O_dB=1V/u\ bar$)	- 64 (-643) - 62 (-623) - 60 (-603)
TOLERANCE	$\pm 3dB$
SENSITIVITY REDUCTION	Within -3.0dB@1.1V
S/N RATIO	More than 40 dB
OUTPUT IMPEDANCE	Low
MAX. OPER. VOLTAGE(VDC)	10 V
OPERATING VOLTAGE (VDC)	1.5 V
CURRENT CONSUMPTION (mA)	Max 0.3
DIMENSIONS (mm)	9.7 x 4.5
TERMINATION	PD = Pad PN = Pin


Typical Frequency Response Curve:



Dimensions:



Schematic Diagram:



$V_s=3.0V$, $R_L = 2.2k\ ohm$

INTERVOX
International ©

International Components Corporation

175 Marcus Blvd., Hauppauge, NY 11788 631-952-9595 FAX 631-952-9597 www.icc107.com

Title:

Electret Condenser Microphone

Intervox Model #

MEO-94P-01-Series

Rev.

Scale:

Date: 06/01/2007

Sheet 1 of 1