

swissbit®

Product Fact Sheet

Industrial CFast Card

F-800 Series

SATA Gen3 – 6.0 Gbit/s, SLC

Commercial and Industrial
Temperature Grade

Date: February 12, 2021
Revision: 1.01



Product Summary

- **Capacities:** 2 GBytes, 4 GBytes, 8 GBytes, 16 GBytes, 32 GBytes, 64 GBytes
- **Form Factor:** CFast-Sized Solid State Drive (36.4 mm x 42.8 mm x 3.6 mm)
- **Interface¹:** SATA Gen3 – 6 Gbit/s (Gen2 – 3 Gbit/s and Gen1 – 1.5 Gbit/s backward compatible)
- **Command Sets:** Supports ATA/ATAPI-8 and ACS-4
- **CFast 2.0 compliant**
- **Performance:**
 - Burst Transfer Rate: Up to 600 MBytes/s in SATA Gen3 – 6.0 Gbit/s
 - Read Performance: Sequential Read up to 319 MBytes/s, Random Read 4K up to 10,400 IOPS
 - Write Performance: Sequential Write up to 150 MBytes/s, Random Write 4K up to 6,800 IOPS
- **Operating Temperature Range²:**
 - Commercial: 0 °C to 70 °C
 - Industrial: -40°C to 85 °C
- **Storage Temperature Range:** -40 °C to 85 °C
- **Operating Voltage:** 3.3 V ± 5%
- **Power typical @ 64 GByte:**
 - Read (Active): 1,250 mW
 - Write (Active): 990 mW
 - Idle: 195 mW
 - Slumber: 50 mW
 - DEVSLP: 2.6 mW
- **Data Retention:** 10 Years @ Life Begin / 1 Year @ Life End
- **Endurance in DiskWritesPerDay (DWPD):**
 - JEDEC Enterprise Workload: up to 4.5
 - JEDEC Client Workload: up to 32
- **Shock / Vibration:** 500 *g* / 20 *g*
- **High-Performance Dual Core 32-Bit Processor with Integrated, Parallel Flash Interface Engines:**
 - Single-Level Cell (SLC) NAND Flash
 - Flexible BCH and GCC ECC engines provide superior error correction performance
- **High Reliability:**
 - Mean Time Between Failure (MTBF): > 2,000,000 hours @ 25°C
 - Data Reliability: < 1 non-recoverable error per 10¹⁶ bits read
 - 30 μinch Gold-Plated Connector

¹ The verification of host system and storage device compatibility is in customer's responsibility. Swissbit can provide guidance and support on request.

² Adequate airflow is required to ensure the temperature, as reported in the S.M.A.R.T. data, does not exceed 120°C (industrial temperature drive) and 105°C (commercial temperature drive) respectively.