

## Stand-alone Gigabit Ethernet Media Converter 1000Base-T to 1000Base-SX/LX

The SGETF Series is a stand-alone media converter that provides an interface between 1000Base-T ports and 1000Base-SX/LX ports, allowing users to integrate fiber optic cabling into 1000Base-T copper environments. Operating at Layer 1, the physical layer, data is passed through the converter at line speed, making it ideal for applications where low latency is essential.



## Key Features

- Auto-MDI/MDIX
- Copper & Fiber Auto-Negotiation
- Transparent Link Pass Through
- Automatic Link Restoration
- Pause
- Remote Fault Detect

## Specifications

Standards	IEEE 802.3ab IEEE 802.3z
6-position Switch	SW1: Remote Fiber Fault Detect (Down=Enabled) SW2: Symmetric Pause SW3: Asymmetric Pause SW4: Transparent Link Pass Through (UP=Enabled) SW5: Fiber Auto-Negotiation (Down=Enabled) SW6: Loopback (Down=Enabled)
Status LEDs	PWR (Power): Steady green LED indicates connection to external AC power RXF (Fiber receive): Flashing LED indicates reception of data on fiber link LKF (Fiber link): Steady LED indicates fiber link connection RXC (Copper receive): Flashing LED indicates reception of data on copper link LKC (Copper link): Steady LED indicates copper link connection
Dimensions	Width: 3.25" [82.55 mm] Depth: 4.8" [121.92 mm] Height: 1" [25 mm]
Power Consumption	5.4W, 450mA @ 12VDC
Power Supply	External AC/DC required; 12 VDC, 0.8A min Output; 120-240 VAC input
Environment	Operating: 0°C to 50°C Humidity: 5% to 95% (non-condensing) Altitude: 0 – 10,000 ft.
Weight	2 lbs. [0.90 kg]
MTBF	382,000 hours (MIL217F2 V5.0) (MIL-HDBK-217F) 1,345,000 hours (Bellcore7 V5.0)
Certifications	Safety: Wall Mount Power Supply: UL Listed, cUL Listed (Canada); FCC Class A, CISPR22/EN55022 Class A, EN55024, EN61000, CE Mark
Warranty	Lifetime

## Ordering Information

### SGETF1013-110

1000Base-T (RJ-45) [100 m/328 ft.] to 1000Base-SX 850nm multimode (SC) [62.5/125 µm fiber: 220 m/722 ft.] Link Budget: 7.0 dB  
[50/125 µm fiber: 550 m/1804 ft.] Link Budget: 7.0 dB

### SGETF1039-110

1000Base-T (RJ-45) [100 m/328 ft.] to 1000Base-SX 850nm multimode (LC) (via TN-SFP-SX) [62.5/125 µm fiber: 220 m/722 ft.] Link Budget: 8.0 dB [50/125 µm fiber: 550 m/1804 ft.] Link Budget: 8.0 dB

### SGETF1014-110

1000Base-T (RJ-45) [100 m/328 ft.] to 1000Base-LX 1310nm single mode (SC) [10 km/6.2 mi.] Link Budget: 10.5 dB

### SGETF1040-110

1000Base-T (RJ-45) [100 m/328 ft.] to SFP slot (empty)

## Optional Accessories (sold separately)

### SFP Modules

## Wide Input (24 - 60 VDC) Power Supplies

### SPS-2460-PS

Piggy Back Power Supply

### SPS-2460-SA

Stand-Alone Power Supply

## Mounting Options (sold separately)

### E-MCR-05

12-slot Media Converter Rack

### RMS19-SA4-02

4-slot Media Converter Shelf

### WMBD

DIN Rail Bracket 5" [127 mm]

### WMBD-F

DIN Rail Bracket (flat) 3.3" [84 mm]

### WMBL

Wall Mount Bracket 4" [102 mm]

### WMBV

Vertical Wall Mount Bracket 5" [127 mm]

## Power Supply Included

To order the corresponding country specific power supply, add the extension from the list below to the end of the SKU; Ex: SGETF1013-110-NA

### -NA = Country Code

- |                     |                      |
|---------------------|----------------------|
| -NA = North America | -LA = Latin America  |
| -EU = Europe        | -UK = United Kingdom |
| -SA = South Africa  | -JP = Japan          |
| -OZ = Australia     | -BR = Brazil         |