

PRODUCT SUMMARY

SKY16706-11: Dual Coupler Module

Applications

- 2G/3G/4G multimode cellular applications
- Supports GSM/WCDMA/HSPA+/LTE/CDMA2000/EVDO applications

Features

- Dual bidirectional couplers
- Low insertion loss (0.22 dB typical at 2690 MHz)
- 25 dB coupling factor at 824 to 2690 MHz
- 25 dB directivity
- High linearity with low harmonics
- Programmable low-pass filtering in the coupled paths to reject 2.4 GHz and 5 GHz ISM blockers
- Programmable attenuators; 4 programmable steps: 0 dB, 3 dB, 6 dB, and 9 dB state
- Supply voltage range of 2.5 V to +4.8 V
- Integrated MIPI RFFE interface
- Small, lead (Pb)-free and RoHS-compliant, 16-lead surface mount package (1.6 × 1.6 × 0.54 mm) (MSL3 @ 260 °C per JEDEC J-STD-020)



Skyworks Green™ products are compliant with all applicable legislation and are halogen-free. For additional information, refer to *Skyworks Definition of Green™*, document number SQ04-0074.




Figure 1. SKY16706-11 Functional Block Diagram

Description

The SKY16706-11 is a dual coupler module (DCM) that consists of two bidirectional couplers with coupled path filtered with a filter optimized for 2.4 GHz and 5 GHz rejection. SKY16706-11 has 50 Ω input and output impedance with internal DC blocking and minimal number of external support components. The DCM is targeted for use in mobile applications. It is compatible with 3GPP GSM, WCDMA, LTE and LTE-A standards and supports the B1, B2, B3, B4, B7, B30, B34, B39, B38, B40, and B41 service bands: for the cellular part. It also supports GPS/GNSS/Beidou localization standards.

The SKY16706-11 is packaged in a compact 16-lead, 1.6 × 1.6 × 0.54 mm surface mount package that meets requirements for board-level assembly.

No external DC blocking capacitors are required on the RF paths as long as no DC voltage is applied. The DCM can operate over the temperature range of -35 °C to +90 °C.

A functional block diagram is shown in Figure 1.

Ordering Information

Model Name	Manufacturing Part Number	Evaluation Board Part Number
SKY16706-11: 2.4 GHz, Dual Coupler Module	SKY16706-11	SKY16706-11-EVB

Copyright © 2016 Skyworks Solutions, Inc. All Rights Reserved.

Information in this document is provided in connection with Skyworks Solutions, Inc. (“Skyworks”) products or services. These materials, including the information contained herein, are provided by Skyworks as a service to its customers and may be used for informational purposes only by the customer. Skyworks assumes no responsibility for errors or omissions in these materials or the information contained herein. Skyworks may change its documentation, products, services, specifications or product descriptions at any time, without notice. Skyworks makes no commitment to update the materials or information and shall have no responsibility whatsoever for conflicts, incompatibilities, or other difficulties arising from any future changes.

No license, whether express, implied, by estoppel or otherwise, is granted to any intellectual property rights by this document. Skyworks assumes no liability for any materials, products or information provided hereunder, including the sale, distribution, reproduction or use of Skyworks products, information or materials, except as may be provided in Skyworks Terms and Conditions of Sale.

THE MATERIALS, PRODUCTS AND INFORMATION ARE PROVIDED “AS IS” WITHOUT WARRANTY OF ANY KIND, WHETHER EXPRESS, IMPLIED, STATUTORY, OR OTHERWISE, INCLUDING FITNESS FOR A PARTICULAR PURPOSE OR USE, MERCHANTABILITY, PERFORMANCE, QUALITY OR NON-INFRINGEMENT OF ANY INTELLECTUAL PROPERTY RIGHT; ALL SUCH WARRANTIES ARE HEREBY EXPRESSLY DISCLAIMED. SKYWORKS DOES NOT WARRANT THE ACCURACY OR COMPLETENESS OF THE INFORMATION, TEXT, GRAPHICS OR OTHER ITEMS CONTAINED WITHIN THESE MATERIALS. SKYWORKS SHALL NOT BE LIABLE FOR ANY DAMAGES, INCLUDING BUT NOT LIMITED TO ANY SPECIAL, INDIRECT, INCIDENTAL, STATUTORY, OR CONSEQUENTIAL DAMAGES, INCLUDING WITHOUT LIMITATION, LOST REVENUES OR LOST PROFITS THAT MAY RESULT FROM THE USE OF THE MATERIALS OR INFORMATION, WHETHER OR NOT THE RECIPIENT OF MATERIALS HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

Skyworks products are not intended for use in medical, lifesaving or life-sustaining applications, or other equipment in which the failure of the Skyworks products could lead to personal injury, death, physical or environmental damage. Skyworks customers using or selling Skyworks products for use in such applications do so at their own risk and agree to fully indemnify Skyworks for any damages resulting from such improper use or sale.

Customers are responsible for their products and applications using Skyworks products, which may deviate from published specifications as a result of design defects, errors, or operation of products outside of published parameters or design specifications. Customers should include design and operating safeguards to minimize these and other risks. Skyworks assumes no liability for applications assistance, customer product design, or damage to any equipment resulting from the use of Skyworks products outside of stated published specifications or parameters.

Skyworks and the Skyworks symbol are trademarks or registered trademarks of Skyworks Solutions, Inc., in the United States and other countries. Third-party brands and names are for identification purposes only, and are the property of their respective owners. Additional information, including relevant terms and conditions, posted at www.skyworksinc.com, are incorporated by reference.