SM606A44400

Hyde Park, Ultrasonic sensor, analog, voltage (V), 18 mm barrel, 15 24 V DC



Main

| Range of product | Hyde Park |
|---------------------------------|---|
| Sensor Type | Ultrasonic sensor |
| Series name | Superprox 600 |
| Device short name | SM606 |
| Sensor design | Cylindrical M18 |
| [Sn] nominal sensing distance | 4.00 in (101.6 mm) |
| Type of sensing window | Fixed |
| Material | Plastic |
| Enclosure Material | ULTEM |
| Front material | Silicone rubber |
| Type of output signal | Analog |
| ISO thread | M18 x 1 |
| Wiring Technique | 4-wire |
| [Us] rated supply voltage | 1524 V DC overload and short-circuit protection |
| Supply voltage limits | 1328 V DC |
| Analogue output range | 010 V inverse |
| Electrical connection | Cable, 9.84 ft (3 m) |
| Product Specific Application | Analog output |
| | |

Complementary

| [Sd] sensing range 1.254.00 in (31.7101.6 mm) Blind zone 0.75 in (19 mm) Transmission frequency 500 kHz Beam angle 10 ° Minimum size of detected object Cylinder diameter 1.59 mm - up to 63.5 mm sensing distance Current Consumption 50 mA Maximum switching current 100 mA reverse polarity protection Height 0.71 in (18 mm) Width 0.71 in (18 mm) Depth 0.71 in (18 mm) Length 2.55 in (64.77 mm) Product Weight 0.37 lb(US) (0.17 kg) | | | |
|---|---------------------------------|--|--|
| Transmission frequency 500 kHz Beam angle 10 ° Minimum size of detected object Cylinder diameter 1.59 mm - up to 63.5 mm sensing distance Current Consumption 50 mA Maximum switching current 100 mA reverse polarity protection Height 0.71 in (18 mm) Width 0.71 in (18 mm) Depth 0.71 in (18 mm) Length 2.55 in (64.77 mm) | [Sd] sensing range | 1.254.00 in (31.7101.6 mm) | |
| Beam angle 10 ° Minimum size of detected object Cylinder diameter 1.59 mm - up to 63.5 mm sensing distance Current Consumption 50 mA Maximum switching current 100 mA reverse polarity protection Height 0.71 in (18 mm) Width 0.71 in (18 mm) Depth 0.71 in (18 mm) Length 2.55 in (64.77 mm) | Blind zone | 0.75 in (19 mm) | |
| Minimum size of detected object Current Consumption 50 mA Maximum switching current 100 mA reverse polarity protection Height 0.71 in (18 mm) Width 0.71 in (18 mm) Depth 0.71 in (18 mm) Length 2.55 in (64.77 mm) | Transmission frequency | 500 kHz | |
| Current Consumption 50 mA Maximum switching current 100 mA reverse polarity protection Height 0.71 in (18 mm) Width 0.71 in (18 mm) Depth 0.71 in (18 mm) Length 2.55 in (64.77 mm) | Beam angle | 10 ° | |
| Maximum switching current 100 mA reverse polarity protection Height 0.71 in (18 mm) Width 0.71 in (18 mm) Depth 0.71 in (18 mm) Length 2.55 in (64.77 mm) | Minimum size of detected object | Cylinder diameter 1.59 mm - up to 63.5 mm sensing distance | |
| Height 0.71 in (18 mm) Width 0.71 in (18 mm) Depth 0.71 in (18 mm) Length 2.55 in (64.77 mm) | Current Consumption | 50 mA | |
| Width 0.71 in (18 mm) Depth 0.71 in (18 mm) Length 2.55 in (64.77 mm) | Maximum switching current | 100 mA reverse polarity protection | |
| Depth 0.71 in (18 mm) Length 2.55 in (64.77 mm) | Height | 0.71 in (18 mm) | |
| Length 2.55 in (64.77 mm) | Width | 0.71 in (18 mm) | |
| | Depth | 0.71 in (18 mm) | |
| Product Weight 0.37 lb(US) (0.17 kg) | Length | 2.55 in (64.77 mm) | |
| | Product Weight | 0.37 lb(US) (0.17 kg) | |

Environment

| Product Certifications | UL | |
|---------------------------------------|--|--|
| Marking | CE | |
| NEMA degree of protection | NEMA 4X indoor use only) | |
| IP degree of protection | IP67 | |
| Ambient Air Temperature for Operation | 32140 °F (060 °C) | |
| Ambient Air Temperature for Storage | -40212 °F (-40100 °C) | |
| Relative humidity | 100 % without condensation | |
| Vibration resistance | +/-1 mm 1055 Hz)IEC 60068-2-6 | |
| Shock resistance | 30 gn in all 3 axes 11 ms IEC 60068-2-27 | |
| Resistance to electromagnetic fields | 9.14 V/m (10 V/m) level 3 IEC 61000-4-3 | |
| Resistance to fast transients | 1 kV level 3 IEC 61000-4-4 | |

Ordering and shipping details

| Category | 22490 - SENSORS-ULTRASONIC (XX5,6) | |
|-----------------------|------------------------------------|--|
| Discount Schedule | DS2 | |
| GTIN | 03389119100601 | |
| Nbr. of units in pkg. | 1 | |
| Package weight(Lbs) | 0.37 lb(US) (0.17 kg) | |
| Returnability | No | |
| Country of origin | US | |

Offer Sustainability

| California proposition 65 | WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |
|---------------------------|---|
| REACh Regulation | ☑ REACh Declaration |
| EU RoHS Directive | Not applicable, out of EU RoHS legal scope |

Contractual warranty

| | · · | |
|----------|-----------|--|
| Warranty | 18 months | |
| | | |