

### Main

|                           |                             |
|---------------------------|-----------------------------|
| Range of Product          | Hyde Park                   |
| Sensor Type               | Ultrasonic sensor           |
| Series name               | Standard format             |
| Device short name         | SM902                       |
| Sensor design             | Ø 30 mm                     |
| Material                  | Stainless steel             |
| [Us] rated supply voltage | 12...24 V DC                |
| Electrical connection     | 1 cable                     |
| [Sd] sensing range        | 0.39...6.56 ft (0.12...2 m) |
| IP degree of protection   | IP66                        |

### Complementary

|                        |         |
|------------------------|---------|
| Type of sensing window | Fixed   |
| Enclosure Material     | Plastic |
| Transmission frequency | 75 kHz  |
| Maximum delay response | 35 ms   |

### Ordering and shipping details

|                       |                                    |
|-----------------------|------------------------------------|
| Category              | 22490 - SENSORS-ULTRASONIC (XX5,6) |
| Discount Schedule     | DS2                                |
| GTIN                  | 03389119114004                     |
| Nbr. of units in pkg. | 1                                  |
| Package weight(Lbs)   | 0.19 lb(US) (0.09 kg)              |
| Returnability         | No                                 |
| Country of origin     | US                                 |

### Offer Sustainability

|                           |                                                                                                                                                                                                                                                                                                                                                                                   |
|---------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| California proposition 65 | WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a> |
| EU RoHS Directive         | Not applicable, out of EU RoHS legal scope                                                                                                                                                                                                                                                                                                                                        |

### Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.