SM950A700000STS

Hyde Park, Ultrasonic sensor, discrete, 30 mm barrel, 12 24 V DC



Main

Range of product	Hyde Park
Sensor Type	Ultrasonic sensor
Series name	Superprox 900
Device short name	SM950
Sensor design	Cylindrical M30
[Sn] nominal sensing distance	3.28 ft (1 m)
Type of sensing window	Adjustable
Material	Stainless steel
Enclosure Material	Stainless steel 303
Front material	Stainless steel 304
Type of output signal	Discrete
Discrete output function	1 NO
ISO thread	M30 x 1.5
Wiring Technique	4-wire
[Us] rated supply voltage	1224 V DC overload and short-circuit protection
Supply voltage limits	1028 V DC
Discrete output type	PNP/NPN
Electrical connection	1 male connector M12 4 pins
Product Specific Application	Discrete proximity

Complementary

o in promortion y		
[Sd] sensing range	0.393.28 ft (0.121 m)	
Maximum differential travel	0.10 in (2.5 mm)	
Blind zone	4.72 in (120 mm)	
Transmission frequency	200 kHz	
Repeat accuracy	0.87 %	
Beam angle	10 °	
Minimum size of detected object	Cylinder diameter 1.6 mm - up to 305 mm sensing distance	
Current Consumption	100 mA	
Maximum switching current	100 mA reverse polarity protection	
Height	1.18 in (30 mm)	
Width	1.37 in (34.7 mm)	
Depth	1.18 in (30 mm)	
Length	3.78 in (96 mm)	
Net Weight	1.98 lb(US) (0.9 kg)	

Environment

Product Certifications	UL	
Marking	CE	
NEMA degree of protection	NEMA 4X indoor use only)	
IP degree of protection	IP67	
Ambient air temperature for operation	-4122 °F (-2050 °C)	
Ambient Air Temperature for Storage	-4176 °F (-2080 °C)	
Relative humidity	100 % without condensation	
Vibration resistance	+/-1 mm 1055 Hz)IEC 60068-2-6	

Shock resistance	30 gn in all 3 axes 11 ms IEC 60068-2-27
Resistance to electromagnetic fields	9.14 V/m (10 V/m) level 3 IEC 61000-4-3
Resistance to fast transients	1 kV level 3 IEC 61000-4-4
Ordering and shipping details	
Category	22490 - SENSORS-ULTRASONIC (XX5,6)
Discount Schedule	DS2
GTIN	3389119117913
Nbr. of units in pkg.	1
Package weight(Lbs)	11.84 oz (335.658 g)
Returnability	No
Country of origin	US
Packing Units Unit Type of Package 1	PCE
Package 1 Height	1.80 in (4.572 cm)
Package 1 width	3.90 in (9.906 cm)
Package 1 Length	5.30 in (13.462 cm)
Offer Sustainability	
California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	REACh Declaration
EU RoHS Directive	Not applicable, out of EU RoHS legal scope

Contractual warranty

Warranty	18 months
•	