## SM952AC10006LE

Hyde Park, Ultrasonic sensor, dual level, pump in latch, 30 mm barrel, 12 24 V DC



## Main

Range of product	Hyde Park
Sensor Type	Ultrasonic sensor
Series name	Superprox 900
Device short name	SM952
Sensor design	Cylindrical M30
[Sn] nominal sensing distance	13.12 ft (4 m)
Type of sensing window	Adjustable
Material	Plastic
Enclosure Material	ULTEM
Front material	Glass epoxy
Type of output signal	Discrete
Discrete output function	1 NO
ISO thread	M30 x 1.5
Wiring Technique	4-wire
[Us] rated supply voltage	1224 V DC overload and short-circuit protection
Supply voltage limits	1028 V DC
Discrete output type	PNP/NPN
Electrical connection	1 male connector M12 4 pins
Product Specific Application	Dual-level - pump-in latch

## Complementary

[Sd] sensing range	0.9813.12 ft (0.34 m)
Maximum differential travel	0.10 in (2.5 mm)
Blind zone	7.99 in (203 mm)
Transmission frequency	75 kHz
Minimum size of detected object	Cylinder diameter 1.6 mm - up to 305 mm sensing distance
Current Consumption	100 mA
Maximum switching current	100 mA reverse polarity protection
Height	1.18 in (30 mm)
Width	1.70 in (43.18 mm)
Depth	1.18 in (30 mm)
Length	4.62 in (117.3 mm)
Product Weight	1.98 lb(US) (0.9 kg)

## Environment

Product Certifications	UL	
Marking	CE	
NEMA degree of protection	NEMA 4X indoor use only)	
IP degree of protection	IP67	
Ambient Air Temperature for Operation	-4140 °F (-2060 °C)	
Ambient Air Temperature for Storage	-4176 °F (-2080 °C)	
Relative humidity	100 % without condensation	
Vibration resistance	+/-1 mm 1055 Hz)IEC 60068-2-6	
Shock resistance	30 gn in all 3 axes 11 ms IEC 60068-2-27	

Resistance to electromagnetic fields	9.14 V/m (10 V/m) level 3 IEC 61000-4-3	
Resistance to fast transients	1 kV level 3 IEC 61000-4-4	
Ordering and shipping details		
Category	22490 - SENSORS-ULTRASONIC (XX5,6)	
Discount Schedule	DS2	
GTIN	03389119118255	
Nbr. of units in pkg.	1	
Package weight(Lbs)	0.08 lb(US) (0.04 kg)	
Returnability	No	
Country of origin	us	
Offer Sustainability		
California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov	
EU RoHS Directive	Not applicable, out of EU RoHS legal scope	
Contractual warranty		
Warranty	18 months	