

## 2N4302, 2N4303, 2N4304 N-Channel JFET

### Features

- InterFET [N0026S Geometry](#)
- Low Noise: 4 nV/√Hz Typical
- Low Leakage: 10pA Typical
- RoHS Compliant
- SMT, TH, and Bare Die Package options.



### Applications

- VHS Amplifiers
- Small Signal Amplifiers
- Oscillators
- Mixers



### Description

The -30V InterFET 2N4302, 2N4303, and 2N4304 are targeted for small signal amplifiers, mixers and oscillators. Gate leakages are typically less than 10pA at room temperatures.

SOT23 Top View



TO-92 Bottom View



### Product Summary

Parameters	2N4302 Min	2N4303 Min	2N4304 Min	Unit
$BV_{GSS}$ Gate to Source Breakdown Voltage	-30	-30	-30	V
$I_{DSS}$ Drain to Source Saturation Current	0.5	4	0.5	mA
$V_{GS(off)}$ Gate to Source Cutoff Voltage	-4 (Max)	-6 (Max)	-10 (Max)	V
$G_{FS}$ Forward Transconductance	1	2	1	mS

### Ordering Information Custom Part and Binning Options Available

Part Number	Description	Case	Packaging
2N4302; 2N4303; 2N4304	Through-Hole	TO-92	Bulk
SMP4302; SMP4303; SMP4304	Surface Mount	SOT23	Bulk
SMP4302TR; SMP4303TR; SMP4304TR	7" Tape and Reel: Max 3,000 Pieces 13" Tape and Reel: Max 9,000 Pieces	SOT23	Minimum 1,000 Pieces Tape and Reel
2N4302COT; 2N4303COT; 2N4304COT	Chip Orientated Tray (COT Waffle Pack)	COT	400/Waffle Pack
2N4302CFT; 2N4303CFT; 2N4304CFT	Chip Face-up Tray (CFT Waffle Pack)	CFT	400/Waffle Pack



**Disclaimer:** It is the Buyers responsibility for designing, validating and testing the end application under all field use cases and extreme use conditions. Guaranteeing the application meets required standards, regulatory compliance, and all safety and security requirements is the responsibility of the Buyer. These resources are subject to change without notice.

## Electrical Characteristics

### Maximum Ratings (@ T<sub>A</sub> = 25°C, Unless otherwise specified)

Parameters	Value	Unit
V <sub>RGS</sub> Reverse Gate Source and Gate Drain Voltage	-30	V
I <sub>FG</sub> Continuous Forward Gate Current	10	mA
P <sub>D</sub> Continuous Device Power Dissipation	300	mW
P Power Derating	2	mW/°C
T <sub>J</sub> Operating Junction Temperature	-55 to 125	°C
T <sub>STG</sub> Storage Temperature	-65 to 150	°C

### Static Characteristics (@ T<sub>A</sub> = 25°C, Unless otherwise specified)

Parameters	Conditions	2N4302		2N4303		2N4304		Unit
		Min	Max	Min	Max	Min	Max	
V <sub>(BR)GSS</sub> Gate to Source Breakdown Voltage	V <sub>DS</sub> = 0V, I <sub>G</sub> = -1μA	-30		-30		-30		V
I <sub>GSS</sub> Gate to Source Reverse Current	V <sub>GS</sub> = -15V, V <sub>DS</sub> = 0V		-1		-1		-1	nA
V <sub>GS(OFF)</sub> Gate to Source Cutoff Voltage	V <sub>DS</sub> = 20V, I <sub>D</sub> = 10nA		-4		-6		-10	V
I <sub>DSS</sub> Drain to Source Saturation Current	V <sub>DS</sub> = 20V, V <sub>GS</sub> = 0V (Pulsed)	0.5	5	4	10	0.5	15	mA

### Dynamic Characteristics (@ T<sub>A</sub> = 25°C, Unless otherwise specified)

Parameters	Conditions	2N4302		2N4303		2N4304		Unit
		Min	Max	Min	Max	Min	Max	
G <sub>FS</sub> Forward Transconductance	V <sub>DS</sub> = 20V, V <sub>GS</sub> = 0V, f = 1kHz	1		2		1		mS
C <sub>iss</sub> Input Capacitance	V <sub>DS</sub> = 20V, V <sub>GS</sub> = 0V, f = 1MHz		6		6		6	pF
C <sub>rss</sub> Reverse Transfer Capacitance	V <sub>DS</sub> = ( ), V <sub>GS</sub> = 0V, f = 1MHz		2 (15)		2 (20)		3 (20)	pF V

## SOT23 (TO-236AB) Mechanical and Layout Data

### Package Outline Data



1. All linear dimensions are in millimeters.
2. Package weight approximately 0.12 grams
3. Molded plastic case UL 94V-0 rated
4. For Tape and Reel specifications refer to InterFET CTC-021 Tape and Reel Specification, Document number: IF39002
5. Bulk product is shipped in standard ESD shipping material
6. Refer to JEDEC standards for additional information.

### Suggested Pad Layout



1. All linear dimensions are in millimeters.
2. The suggested land pattern dimensions have been provided for reference only. A more robust pattern may be desired for wave soldering.