


# SOM-3567

## Intel® Atom™ E3800 & Celeron® Processor QSeven CPU Module



Windows Embedded

iManager WISE-PaaS/RMM



### Features

- Intel® Atom® E3800 and Celeron® Processor Series
- Qseven® 2.1 Specification Compatible
- Onboard Dual Channel DDR3L-1333 up to 8GB, eMMC up to 32GB
- LVDS and HDMI/DP support H.264, MPEG2 HW Decode/Encode
- GbE, 3 PCIe x1, 1 USB3.0, 6 USB2.0
- iManager WISE-PaaS/RMM, and Embedded Software APIs

Software APIs:



Watchdog



PC



SMBus



H/W Monitor



GPIO




Brightness Control

### Specifications

Compliance	Form-Factor	QSeven 70 x 70 mm							
	Pin-out Type	QSeven 2.1							
Platform	CPU	Atom® E3845	Atom® E3827	Atom® E3825	Atom® E3815	Atom® E3805	Celeron® J1900	Celeron® N2807	
	Base Frequency	1.91GHz	1.75GHz	1.33GHz	1.46GHz	1.33GHz	2.00GHz	1.58GHz	
	Burst Frequency	-	-	-	-	-	2.42GHz	2.16GHz	
	Core/Thread	4/4	2/2	2/2	1/1	2/2	4/4	2/2	
	LLC	2MB	1MB	1MB	512KB	1MB	2MB	1MB	
	CPU TDP	10W	8W	6W	5W	3W	10W	4.3W	
	Chipset	N/A							
	BIOS	AMI EFI BIOS							
Memory	Technology	DDR3L-1333	DDR3L-1333	DDR3L-1066	DDR3L-1066	DDR3L-1066	DDR3L-1333	DDR3L-1333	
	ECC Support	Not support							
	Channel/Socket	Onboard Single/Dual Channels							
	Max. Capacity	Up to 8GB							
Graphics	Controller	Intel® Gen 7				No graphic			
	Base/Turbo Freq.	542MHz	542MHz	533MHz	400 MHz	No graphic	688 MHz	313MHz	
	Graphics Burst Frequency	792MHz	792MHz	-	-	No graphic	854 MHz	750MHz	
	Graphics Memory	Up to 1720MB DVMT				No graphic			
	3D/HW Acceleration	DX11, OGL3.2, OCL1.1, and H.264/AVC, VC-1, MPEG2 HW Decode/Encode				No graphic			
Display	LCD	LVDS: Dual channel 18/24-bit, up to 1920 x 1080							
	DDI	1 DDI support HDMI/DVI/DP configurable							
		HDMI 1.4b: 3840 x 2160 @ 30Hz or 2560 x 1600 @ 60Hz, 24 bpp							
		DVI: up to 1920 x 1080 @ 60Hz							
Multiple Display	DP 1.1a: 3840 x 2160 @ 30Hz or 2560 x 1600 @ 60Hz, 24 bpp								
Expansion	PCI Express	3 PCIe x1, optional 4 ports while remove Ethernet; Support x1, x2, x4 configurable							
	Audio Interface	HD Audio							
	LPC	Yes							
Serial Bus	SMBus	Yes							
	I <sup>2</sup> C Bus	Yes							
Ethernet	Controller	Intel® i210IT							
	Speed	10/100/1000 Mbps							
Onboard Storage	eMMC	eMMC4.51 up to 32GB							
	SATA	2 Ports, Support Gen3.1 (6Gb/s) and Gen2 (3 Gb/s) or Gen 1(1.5 Gb/s)							
	USB3.0	1 Port							
I/O	USB2.0	6 ports							
	SPI Bus	Support SPI BIOS EEPROM							
	GPIO	Not support GPIO mux with LPC							
	Watchdog	Multi-stage Watchdog Timer Output, 65536 level, 0 ~ 65535 sec							
	COM Port	4-wire COM 2 Ports (1 on MFG pins), optional support GPIO							
	Smart Fan	1 port							
	Power	Type	ATX: Vin, VSB, AT: Vin						
		Supply Voltage	Vin: 5V±5%, VSB: 5V±5%, RTC Battery: 2.0-3.3V						
Power Consumption		TBD							
Environment	Temperature	0 ~ 60° C (32 ~ 140° F)							
	Humidity	Operating: 40° C @ 95% relative humidity, non-condensing							
		Storage: 60° C @ 95%relative humidity, non-condensing							
Mechanical	Vibration Resistance	3.5 Grms							
	Dimensions	70 x 70 mm (2.75" x 2.75")							

## Block Diagram



## Ordering Information

Part No.	CPU	Freq.	Core	CPU TDP	Memory	eMMC	Thermal Solution	Operating Temperature
SOM-3567CS0CB-S9A1	Atom E3845	1.91GHz	4C	10W	4GB	N/A	Passive	0 ~ 60 °C
SOM-3567CS0CB-U0A1	Celeron J1900	2.00GHz	4C	10W	4GB	N/A	Passive	0 ~ 60 °C
SOM-3567CS0CB-U1A1	Celeron N2930	1.83GHz	4C	7.5W	4GB	N/A	Passive	0 ~ 60 °C
SOM-3567BS0CB-U4A1	Celeron N2807	1.58GHz	2C	4.3W	2GB	N/A	Passive	0 ~ 60 °C
SOM-3567CMBXB-S9A1	Atom E3845	1.91GHz	4C	10W	4GB	32GB	Passive	-40 ~ 85 °C
SOM-3567BS0XB-S7A1	Atom E3827	1.75GHz	2C	8W	2GB	N/A	Passive	-40 ~ 85 °C
SOM-3567BS0XB-S3A1	Atom E3825	1.33GHz	2C	6W	2GB	N/A	Passive	-40 ~ 85 °C
SOM-3567BS0XB-S5A1	Atom E3815	1.46GHz	1C	5W	2GB	N/A	Passive	-40 ~ 85 °C
SOM-3567CSAXB-S2A1	Atom E3805	1.33GHz	2C	3W	4GB	16GB	Passive	-40 ~ 85 °C

\*Any other sku or combination is project based support. Please contact sales for details.

## Packing List

Part No.	Description	Quantity
-	SOM-3567 Qseven CPU Module	1
1960076583N000	Heatspreader	1

## Optional Accessories

Part No.	Description
1960058145N001	Semi-Heatsink, 70L x 63W x 13.2H (0 ~ 60° C)
1960061089N001	Semi-Heatsink, 70L x 63W x 34H (-40 ~ 85° C)

## Development Board

Part No.	Description	Quantity
SOM-DB3520-00A1E	Qseven Development Board	1

## Embedded OS

OS	Part No.	Description
WES7	2070014541	img WES7E SOM-3567 X64 V5.7.0 Eng