# SPC56ELADPT144S



#### Data brief

## SPC56ELxx microcontroller family evaluation board



Product status link

SPC56ELADPT144S		
Product summary		
Order code	SPC56ELADPT144S	
Reference	Mini module for: SPC56EL60L5 <sup>(1)</sup>	
Order code	SPC56XXMB	
Reference	Mother board for SPC56xx family of devices	

 The MCU is not included, it must be purchased separately. Please contact your sales representative for more details.

#### **Features**

- SPC56xx modular evaluation system
- On/off power switch with LED indicators
- Board power supply: 12 VDC external supply voltage
- Onboard STMicroelectronics L9758 voltage regulator with three simultaneous output at 1.2 V, 3.3 V and 5 V
- Possibility to configure onboard peripherals to operate at 5 V or 3.3 V logic levels, depending on target
- Two CAN channels with jumper enable
  - One CAN channel with High-Speed transceiver and DB9 male connector
  - One CAN channel with Low-Speed Fault Tolerant and High-Speed transceiver (selectable with jumpers) and DB9 male connector
- Two LIN channels with jumper enable
  - One channel with transceiver and pin header connector populated
  - One channel with footprints only
- One SCI channel with jumper enables, transceiver and DB9 female connector
- Two FlexRay channels with jumper enables
  - One channel with transceiver and DB9 male connector
  - One channel with footprint only
  - Four user push buttons with jumper enable and polarity selection
- Four user LED's with jumper enables
- One potentiometer for analog voltage input
- Pin array for accessing all I/O signals
- Expansion connectors for accessing all I/O signals
- Prototyping area with 0.1" spacing and SOIC footprint
- Specifications:
  - Board size 110 mm x 75 mm
  - 12 VDC Center Positive power supply with 2.5/5.5 mm barrel connectory
- Standard connectors to SPC56XXMB

### **Description**

The SPC56ELADPT144S is an evaluation system supporting the STMicroelectronics SPC56ELxx family of automotive microprocessors.

The complete system consists of an SPC56XXMB motherboard and a mini module which plugs directly into the motherboard. Different mini modules are available for evaluating the whole family of devices in all supported packages.

The evaluation system (motherboard and daughter card) allows full access to the CPU, all the CPU's I/O signals, and the motherboard peripherals (such as CAN, SCI and LIN). The mini modules itself can be used as a standalone unit when access to the I/O pins or peripherals is not needed.

The MCU is not included, it must be purchased separately. Please contact your sales representative for more details.

## **Revision history**

Date	Version	Changes
20-Sep-2012	1	Initial release.
		SPC56ELADPT144S was previously in document DM00044221
		(DocID 022591) revision 1.
17-Sep-2013	2	Updated disclaimer.
16-Dec-2019	3	Updated features in cover page.
		Added product status link table and product summary table.
		Minor text changes.

#### Table 1. Document revision history