



Data brief

# SPC572LADPT80S, SPC572LADPT100S microcontroller premium evaluation boards for SPC572Lx



### **Features**

#### SPC572LADPT80S, SPC572LADPT100S

- Open top MCU socket
- Flexible MCU clocking options:
  - 40 MHz crystal EVB clock circuit
  - 8 MHz EVB clock oscillator circuit
  - External clock via SMA connector
- · User reset switch with reset status LEDs
- 14-pin standard JTAG connector
- 34-pin connector for Nexus 2 interface
- 10-pin SIPI connector for Serial Interprocessor Interface
- Minimodule dimension: 127 mm X 114 mm
- Standard connectors to SPC58XXMB/SPC57XXMB

#### SPC58XXMB/SPC57XXMB

- SPC572Lx modular evaluation system
- Single 12 V external power supply
- Four on-board regulators:
  - 5.0 V, 3.3 V and 1.25 V switching regulators
  - 5 V linear regulator for the ADC supplies and references
  - Master power switch and regulator status LEDs
- Two 240-way high-density expansion connectors for MCU daughter cards
- All MCU signals readily accessible at a port-ordered group of 0.1" pitch headers
- RS232/SCI physical interface and standard DB9 female connector
- LINFlexD interface with two different style connectors
- Two high speed CAN-FD channels and two female standard DB9 connectors
- One potentiometer for analog voltage input and four user switches and 4 user LEDs, freely connectable

## Product status link

SPC572LADPT80S

SPC572LADPT100S

Product summary		
Order code	SPC572LADPT80S	
Reference	Daughter card for SPC572Lx MCU in eTQFP80 package. (1)	
Order code	SPC572LADPT100S	
Reference	Daughter card for SPC572Lx MCU in eTQFP100 package. (1)	
Order code	SPC58XXMB	
Reference	Motherboard for SPC58/ SPC57 family devices.	
Order code	SPC57XXMB	
Reference	Motherboard for SPC58/ SPC57 family devices.	

#### The MCU is not included, it must be purchased separately. Please contact your sales representative for more details.

# **Description**

The Premium Evaluation Boards System supports the 32-bit SPC572Lx STMicroelectronics' automotive microcontrollers.

The complete system consists of an SPC58XXMB/SPC57XXMB motherboard and an SPC572LADPTx daughter card which plugs into the motherboard. Different daughter cards are available for evaluating the whole family of device in all supported packages. All daughter cards are similar in design and concept.

The evaluation system (motherboard and daughter card) allows full access to the CPU, all the CPU's I/O signals, and the motherboard peripherals (such as CAN, SCI, LIN and FlexRAY). The daughter card itself can be used as a standalone unit when access to the I/O pins or peripherals is not needed. The MCU is not included, it must be purchased separately. Please contact your sales representative for more details.



# **Revision history**

**Table 1. Document revision history** 

Date	Version	Changes
01-Jul-2015	1	Initial release.
13-Dec-2019	2	Updated features.  Added product status link table and product summary table.  Minor text changes.

DB2624 - Rev 2 page 2/3