

# SQF-ISD

## Industrial SD Card

# SQF-UDM

## Industrial USB Disk Module

NEW



RoHS COMPLIANT 2002/95/EC CE FCC

### Features

- SLC and MLC NAND Flash and wide range temperature support
- Compliant with SD system specification version 2.0 and 3.0
- Write protection feature using mechanical switch
- Shock resistance, anti-vibration and low power consumption

### Specifications

|                               |  |
|-------------------------------|--|
| Connector Type                | SD Card  |
| Flash Type                    | SLC / MLC  |
| Capacity                      | SLC: 1 to 32 GB<br>MLC: 4 to 64 GB                               |
| Sustained R/W Performance (*) | SLC: up to 25/15 MB/sec<br>MLC: up to 22/10 MB/sec               |
| Operating Temperature         | Commercial grade: 0 to +70° C<br>Industrial grade: -40 to +85° C |
| Shock Resistance              | 1,500 G, Peak / 0.5 ms   |
| Vibration Resistance          | 5 G, Peak / 10 ~ 2000 Hz   |
| Endurance                     | > 2,000,000 program/erase cycles                                 |
| Dimensions (mm)               | 32 (L) x 24 (W) x 2.1 (H)  |

(\*) These values are for reference only; they may change according to the flash memory used.

### Ordering Information

| Part No.         | Product Description  |
|------------------|--|
| SQF-ISDS1-XG-86C | Advantech SQFlash SD Card C6 SLC 1/2 G (0 ~ 70° C)             |
| SQF-ISDS1-XG-86E | Advantech SQFlash SD Card C6 SLC 1/2 G (-40 ~ 85° C)           |
| SQF-ISDS1-XG-82C | Advantech SQFlash SD Card C10 SLC 4/8/16/32 G (0 ~ 70° C)      |
| SQF-ISDS1-XG-82E | Advantech SQFlash SD Card C10 SLC 4/8/16/32 G (-40 ~ 85° C)    |
| SQF-ISDM1-XG-82C | Advantech SQFlash SD Card C10 MLC 4/8/16/32/64 G (0 ~ 70° C)   |
| SQF-ISDM1-XG-82E | Advantech SQFlash SD Card C10 MLC 4/8/16/32/64 G (-40 ~ 85° C) |

Note: X stands for different capacities

NEW



RoHS COMPLIANT 2002/95/EC CE FCC

### Features

- Compliant with standard USB specifications
- Built-in EDC/ECC up to 12 random bits error per 512 bytes
- Advanced wear-leveling and block management
- Shock resistance, anti-vibration and low power consumption

### Specifications

|                               |  |
|-------------------------------|--|
| Connector Type                | 10-pin 2.54 mm pitch receptacle housing connector  |
| Flash Type                    | SLC / MLC  |
| Capacity                      | SLC: 1 to 32 GB<br>MLC: 4 to 64 GB                 |
| DC Supply Voltage             | 5V (±10%)  |
| Sustained R/W Performance (*) | SLC: up to 32/26 MB/sec<br>MLC: up to 30/12 MB/sec |
| Operating Temperature         | Commercial Grade: 0 to +70° C                      |
| Shock Resistance              | 2,500 G, Peak / 0.5 ms                             |
| Vibration Resistance          | 20 G, Peak / 80 ~ 2000 Hz                          |
| Endurance                     | > 5,000,000 program/erase cycles                   |
| Dimensions (mm)               | 26.5 x 37.8 x 10.6 (PCB Size)                      |
| Orientation                   | Horizontal   |

(\*) These values are for reference only; they may change according to the flash memory used.

### Ordering Information

| Part No.         | Product Description   |
|------------------|---|
| SQF-UDMS1-1G-HDC | Advantech SQFlash USB DOM SLC 1 G, 1-CH (0 ~ 70° C)             |
| SQF-UDMS1-1G-HDE | Advantech SQFlash USB DOM SLC 1 G, 1-CH (-40 ~ 85° C)           |
| SQF-UDMS2-XG-HDC | Advantech SQFlash USB DOM SLC 2/4/8/16/32 G, 2-CH (0 ~ 70° C)   |
| SQF-UDMS2-XG-HDE | Advantech SQFlash USB DOM SLC 2/4/8/16/32 G, 2-CH (-40 ~ 85° C) |
| SQF-UDMM1-4G-HDC | Advantech SQFlash USB DOM MLC 4 G, 1-CH (0 ~ 70° C)             |
| SQF-UDMM1-4G-HDE | Advantech SQFlash USB DOM MLC 4 G, 1-CH (-40 ~ 85° C)           |
| SQF-UDMM2-XG-HDC | Advantech SQFlash USB DOM MLC 8/16/32/64 G, 2-CH (0 ~ 70° C)    |
| SQF-UDMM2-XG-HDE | Advantech SQFlash USB DOM MLC 8/16/32/64 G, 2-CH (-40 ~ 85° C)  |

Note: X stands for different capacities