

## 8A, 20V - 200V Schottky Barrier Rectifier

### FEATURES

- AEC-Q101 qualified available
- Low forward voltage drop
- Low power loss, high efficiency
- Guard ring for overvoltage protection
- High surge current capability
- RoHS Compliant
- Halogen-free according to IEC 61249-2-21

### APPLICATIONS

- Switching mode power supply (SMPS)
- Adapters
- DC to DC converter

### MECHANICAL DATA

- Case: DO-201AD
- Molding compound meets UL 94V-0 flammability rating
- Terminal: Pure tin plated leads, solderable per J-STD-002
- Meet JESD 201 class 2 whisker test
- Polarity: Indicated by cathode band
- Weight: 1.10g (approximately)

KEY PARAMETERS		
PARAMETER	VALUE	UNIT
$I_F$	8	A
$V_{RRM}$	20 - 200	V
$I_{FSM}$	150	A
$T_{JMAX}$	125, 150	°C
Package	DO-201AD	
Configuration	Single die	



DO-201AD



ABSOLUTE MAXIMUM RATINGS ( $T_A = 25^\circ\text{C}$ unless otherwise noted)											
PARAMETER	SYMBOL	SR 802	SR 803	SR 804	SR 805	SR 806	SR 809	SR 810	SR 815	SR 820	UNIT
Marking code on the device		SR 802	SR 803	SR 804	SR 805	SR 806	SR 809	SR 810	SR 815	SR 820	
Repetitive peak reverse voltage	$V_{RRM}$	20	30	40	50	60	90	100	150	200	V
Reverse voltage, total rms value	$V_{R(RMS)}$	14	21	28	35	42	63	70	105	140	V
Forward current	$I_F$	8									A
Surge peak forward current, 8.3ms single half sine wave superimposed on rated load	$I_{FSM}$	150									A
Critical rate of rise of off-state voltage	dv/dt	10,000									V/ $\mu\text{s}$
Junction temperature	$T_J$	-55 to +125				-55 to +150					°C
Storage temperature	$T_{STG}$	-55 to +150									°C

<b>THERMAL PERFORMANCE</b>			
<b>PARAMETER</b>	<b>SYMBOL</b>	<b>TYP</b>	<b>UNIT</b>
Junction-to-ambient thermal resistance	$R_{\theta JA}$	40	°C/W

<b>ELECTRICAL SPECIFICATIONS</b> ( $T_A = 25^\circ\text{C}$ unless otherwise noted)							
<b>PARAMETER</b>		<b>CONDITIONS</b>	<b>SYMBOL</b>	<b>TYP</b>	<b>MAX</b>	<b>UNIT</b>	
Forward voltage <sup>(1)</sup>	SR802 SR803 SR804	$I_F = 8\text{A}, T_J = 25^\circ\text{C}$	$V_F$	-	0.55	V	
	SR805 SR806			-	0.70	V	
	SR809 SR810			-	0.92	V	
	SR815 SR820			-	1.02	V	
Reverse current @ rated $V_R$ <sup>(2)</sup>	SR802 SR803 SR804 SR805 SR806	$T_J = 25^\circ\text{C}$	$I_R$	-	500	$\mu\text{A}$	
	SR809 SR810 SR815 SR820	$T_J = 100^\circ\text{C}$		-	100	$\mu\text{A}$	
	SR802 SR803 SR804			$T_J = 125^\circ\text{C}$	-	15	mA
	SR805 SR806				-	10	mA
	SR809 SR810 SR815 SR820	-			-	mA	
	SR802 SR803 SR804	-			-	mA	
	SR805 SR806	-		-	mA		
	SR809 SR810 SR815 SR820	-		5	mA		

**Notes:**

1. Pulse test with PW = 0.3ms
2. Pulse test with PW = 30ms

<b>ORDERING INFORMATION</b>		
<b>ORDERING CODE<sup>(1)(2)</sup></b>	<b>PACKAGE</b>	<b>PACKING</b>
SR8x	DO-201AD	1,250 / Tape & Reel
SR8x A0G	DO-201AD	500 / Ammo box
SR8xH	DO-201AD	1,250 / Tape & Reel
SR8xHA0G	DO-201AD	500 / Ammo box


**Notes:**

1. "x" defines voltage from 20V (SR802) to 200V (SR820)
2. "H" means AEC-Q101 qualified


**CHARACTERISTICS CURVES**

( $T_A = 25^\circ\text{C}$  unless otherwise noted)


**Fig.1 Forward Current Derating Curve**




**Fig.2 Typical Junction Capacitance**




**Fig.3 Typical Reverse Characteristics**



**Fig.4 Typical Forward Characteristics**




**Fig.5 Maximum Non-Repetitive Forward Surge Current**




**CHARACTERISTICS CURVES**

( $T_A = 25^\circ\text{C}$  unless otherwise noted)

**Fig.6 Typical Transient Thermal Characteristics**



**PACKAGE OUTLINE DIMENSIONS**



DIM.	Unit (mm)		Unit (inch)	
	Min.	Max.	Min.	Max.
A	25.40	-	1.000	-
B	8.50	9.50	0.335	0.374
C	1.20	1.30	0.047	0.051
D	5.00	5.60	0.197	0.220

**MARKING DIAGRAM**



- P/N = Marking Code
- G = Green Compound
- YWW = Date Code
- F = Factory Code