

# STGB20H60DF, STGF20H60DF, STGP20H60DF

600 V, 20 A high speed  
trench gate field-stop IGBT

Datasheet - production data





Figure 1. Internal schematic diagram



## Features

- High speed switching
- Tight parameters distribution
- Safe paralleling
- Low thermal resistance
- Short-circuit rated
- Ultrafast soft recovery antiparallel diode

## Applications

- Motor control
- UPS, PFC

## Description

This device is an IGBT developed using an advanced proprietary trench gate and field stop structure. This IGBT series offers the optimum compromise between conduction and switching losses, maximizing the efficiency of very high frequency converters. Furthermore, a positive  $V_{CE(sat)}$  temperature coefficient and very tight parameter distribution result in easier paralleling operation.

Table 1. Device summary

| Order codes | Marking   | Packages | Packaging     |
|-------------|-----------|----------|---------------|
| STGB20H60DF | GB20H60DF | D²PAK    | Tape and reel |
| STGF20H60DF | GF20H60DF | TO-220FP | Tube          |
| STGP20H60DF | GP20H60DF | TO-220   | Tube          |

## Contents

|          |                                     |           |
|----------|-------------------------------------|-----------|
| <b>1</b> | <b>Electrical ratings</b>           | <b>3</b>  |
| <b>2</b> | <b>Electrical characteristics</b>   | <b>4</b>  |
| 2.1      | Electrical characteristics (curves) | 7         |
| <b>3</b> | <b>Test circuits</b>                | <b>12</b> |
| <b>4</b> | <b>Package mechanical data</b>      | <b>13</b> |
| <b>5</b> | <b>Packaging mechanical data</b>    | <b>19</b> |
| <b>6</b> | <b>Revision history</b>             | <b>21</b> |

# 1 Electrical ratings

Table 2. Absolute maximum ratings

| Symbol         | Parameter   | TO-220<br>D <sup>2</sup> PAK | TO-220FP          | Unit             |
|----------------|---|------------------------------|-------------------|------------------|
| $V_{CES}$      | Collector-emitter voltage ( $V_{GE} = 0$ )                | 600                          |                   | V                |
| $I_C$          | Continuous collector current at $T_C = 25^\circ\text{C}$  | 40                           | 40 <sup>(1)</sup> | A                |
|                | Continuous collector current at $T_C = 100^\circ\text{C}$ | 20                           | 20 <sup>(1)</sup> | A                |
| $I_{CP}^{(2)}$ | Pulsed collector current                                  | 80                           | 80 <sup>(1)</sup> | A                |
| $V_{GE}$       | Gate-emitter voltage                                      | $\pm 20$                     |                   | V                |
| $I_F$          | Continuous forward current $T_C = 25^\circ\text{C}$       | 40                           | 40 <sup>(1)</sup> | A                |
|                | Continuous forward current at $T_C = 100^\circ\text{C}$   | 20                           | 20 <sup>(1)</sup> |                  |
| $I_{FP}^{(2)}$ | Pulsed forward current                                    | 80                           | 80 <sup>(1)</sup> | A                |
| $P_{TOT}$      | Total dissipation at $T_C = 25^\circ\text{C}$             | 167                          | 37                | W                |
| $T_{STG}$      | Storage temperature range                                 | - 55 to 150                  |                   | $^\circ\text{C}$ |
| $T_J$          | Operating junction temperature                            | - 55 to 175                  |                   |                  |

1. Limited by maximum junction temperature.
2. Pulse width limited by maximum junction temperature and turn-off within RBSOA.

Table 3. Thermal data

| Symbol     | Parameter                              | TO-220<br>D <sup>2</sup> PAK | TO-220FP | Unit                      |
|------------|--|------------------------------|----------|---------------------------|
| $R_{thJC}$ | Thermal resistance junction-case IGBT  | 0.9                          | 4        | $^\circ\text{C}/\text{W}$ |
| $R_{thJC}$ | Thermal resistance junction-case diode | 2.5                          | 5.6      | $^\circ\text{C}/\text{W}$ |
| $R_{thJA}$ | Thermal resistance junction-ambient    | 62.5                         |          | $^\circ\text{C}/\text{W}$ |

## 2 Electrical characteristics

$T_J = 25^\circ\text{C}$  unless otherwise specified.

Table 4. Static

| Symbol                      | Parameter  | Test conditions  | Min. | Typ. | Max. | Unit          |
|-----------------------------|--|--|------|------|------|---------------|
| $V_{(\text{BR})\text{CES}}$ | Collector-emitter breakdown voltage ( $V_{GE} = 0$ ) | $I_C = 2 \text{ mA}$   | 600  |      |      | V             |
| $V_{CE(\text{sat})}$        | Collector-emitter saturation voltage                 | $V_{GE} = 15 \text{ V}, I_C = 20 \text{ A}$                              |      | 1.6  | 2.0  | V             |
|                             |  | $V_{GE} = 15 \text{ V}, I_C = 20 \text{ A}$<br>$T_J = 125^\circ\text{C}$ |      | 1.75 |      |               |
|                             |  | $V_{GE} = 15 \text{ V}, I_C = 20 \text{ A}$<br>$T_J = 175^\circ\text{C}$ |      | 1.8  |      |               |
| $V_{GE(\text{th})}$         | Gate threshold voltage                               | $V_{CE} = V_{GE}, I_C = 1 \text{ mA}$                                    | 5.0  | 6.0  | 7.0  | V             |
| $I_{CES}$                   | Collector cut-off current ( $V_{GE} = 0$ )           | $V_{CE} = 600 \text{ V}$   |      |      | 25   | $\mu\text{A}$ |
| $I_{GES}$                   | Gate-emitter leakage current ( $V_{CE} = 0$ )        | $V_{GE} = \pm 20 \text{ V}$  |      |      | 250  | nA            |

Table 5. Dynamic

| Symbol    | Parameter                    | Test conditions   | Min. | Typ. | Max. | Unit |
|-----------|------------------------------|---|------|------|------|------|
| $C_{ies}$ | Input capacitance            | $V_{CE} = 25 \text{ V}, f = 1 \text{ MHz}, V_{GE} = 0$              | -    | 2750 | -    | pF   |
| $C_{oes}$ | Output capacitance           |   | -    | 110  | -    | pF   |
| $C_{res}$ | Reverse transfer capacitance |   | -    | 65   | -    | pF   |
| $Q_g$     | Total gate charge            | $V_{CC} = 400 \text{ V}, I_C = 20 \text{ A}, V_{GE} = 15 \text{ V}$ | -    | 115  | -    | nC   |
| $Q_{ge}$  | Gate-emitter charge          |   | -    | 22   | -    | nC   |
| $Q_{gc}$  | Gate-collector charge        |   | -    | 45   | -    | nC   |

**Table 6. Switching characteristics (inductive load)**

| Symbol        | Parameter                    | Test conditions  | Min. | Typ. | Max. | Unit             |
|---------------|------------------------------|--|------|------|------|------------------|
| $t_{d(on)}$   | Turn-on delay time           | $V_{CE} = 400 \text{ V}, I_C = 20 \text{ A}, R_G = 10 \Omega, V_{GE} = 15 \text{ V}$                                       |      | 42.5 | -    | ns               |
| $t_r$         | Current rise time            |  |      | 11.9 | -    | ns               |
| (di/dt)on     | Turn-on current slope        |  |      | 1345 | -    | A/ $\mu\text{s}$ |
| $t_{d(on)}$   | Turn-on delay time           | $V_{CE} = 400 \text{ V}, I_C = 20 \text{ A}, R_G = 10 \Omega, V_{GE} = 15 \text{ V}$<br>$T_J = 175 \text{ }^\circ\text{C}$ |      | 42.5 | -    | ns               |
| $t_r$         | Current rise time            |  |      | 13.4 | -    | ns               |
| (di/dt)on     | Turn-on current slope        |  |      | 1180 | -    | A/ $\mu\text{s}$ |
| $t_{r(Voff)}$ | Off voltage rise time        | $V_{CE} = 400 \text{ V}, I_C = 20 \text{ A}, R_G = 10 \Omega, V_{GE} = 15 \text{ V}$                                       |      | 20   | -    | ns               |
| $t_{d(off)}$  | Turn-off delay time          |  |      | 177  | -    | ns               |
| $t_f$         | Current fall time            |  |      | 55   | -    | ns               |
| $t_{r(Voff)}$ | Off voltage rise time        | $V_{CE} = 400 \text{ V}, I_C = 20 \text{ A}, R_G = 10 \Omega, V_{GE} = 15 \text{ V}$<br>$T_J = 175 \text{ }^\circ\text{C}$ |      | 26   | -    | ns               |
| $t_{d(off)}$  | Turn-off delay time          |  |      | 173  | -    | ns               |
| $t_f$         | Current fall time            |  |      | 86   | -    | ns               |
| $t_{sc}$      | Short-circuit withstand time | $V_{CC} \leq 360 \text{ V}, V_{GE} = 15 \text{ V}$   | 3    | 5    | -    | $\mu\text{s}$    |

**Table 7. Switching energy (inductive load)**

| Symbol          | Parameter                 | Test conditions  | Min. | Typ. | Max. | Unit          |
|-----------------|---------------------------|--|------|------|------|---------------|
| $E_{on}^{(1)}$  | Turn-on switching losses  | $V_{CE} = 400 \text{ V}, I_C = 20 \text{ A}, R_G = 10 \Omega, V_{GE} = 15 \text{ V}$                                       | -    | 209  | -    | $\mu\text{J}$ |
| $E_{off}^{(2)}$ | Turn-off switching losses |  | -    | 261  | -    | $\mu\text{J}$ |
| $E_{ts}$        | Total switching losses    |  | -    | 470  | -    | $\mu\text{J}$ |
| $E_{on}^{(1)}$  | Turn-on switching losses  | $V_{CE} = 400 \text{ V}, I_C = 20 \text{ A}, R_G = 10 \Omega, V_{GE} = 15 \text{ V}$<br>$T_J = 175 \text{ }^\circ\text{C}$ | -    | 480  | -    | $\mu\text{J}$ |
| $E_{off}^{(2)}$ | Turn-off switching losses |  | -    | 416  | -    | $\mu\text{J}$ |
| $E_{ts}$        | Total switching losses    |  | -    | 896  | -    | $\mu\text{J}$ |


1. Energy losses include reverse recovery of the diode.
2. Turn-off losses include also the tail of the collector current.

**Table 8. Collector-emitter diode**


| Symbol    | Parameter                | Test conditions   | Min. | Typ.       | Max. | Unit   |
|-----------|--------------------------|---|------|------------|------|--------|
| $V_F$     | Forward on-voltage       | $I_F = 20 \text{ A}$<br>$I_F = 20 \text{ A}, T_J = 175 \text{ }^\circ\text{C}$  | -    | 1.8<br>1.3 | 2.2  | V<br>V |
| $t_{rr}$  | Reverse recovery time    | $V_r = 60 \text{ V}; IF = 20 \text{ A};$<br>$dI_F/dt = 100 \text{ A} / \mu\text{s}$                                       | -    | 90         | -    | ns     |
| $Q_{rr}$  | Reverse recovery charge  |   |      | 110        |      | nC     |
| $I_{rrm}$ | Reverse recovery current |   |      | 2.4        |      | A      |
| $t_{rr}$  | Reverse recovery time    | $V_r = 60 \text{ V}; IF = 20 \text{ A};$<br>$dI_F/dt = 100 \text{ A} / \mu\text{s}$<br>$T_J = 175 \text{ }^\circ\text{C}$ | -    | 180        | -    | ns     |
| $Q_{rr}$  | Reverse recovery charge  |   | -    | 466        | -    | nC     |
| $I_{rrm}$ | Reverse recovery current |   | -    | 5.2        | -    | A      |

## 2.1 Electrical characteristics (curves)


**Figure 2. Output characteristics ( $T_J = 25^\circ\text{C}$ )**




**Figure 3. Output characteristics ( $T_J = 175^\circ\text{C}$ )**




**Figure 4. Transfer characteristics**




**Figure 5. Normalized  $V_{GE(\text{th})}$  vs junction temperature**




**Figure 6. Collector current vs. case temperature for D<sup>2</sup>PAK and TO-220**




**Figure 7. Collector current vs. case temperature for TO-220FP**




**Figure 8. Collector current vs. frequency for D<sup>2</sup>PAK and TO-220**




**Figure 9. Collector current vs. frequency for TO-220FP**















**Figure 10. Power dissipation vs. case temperature for D<sup>2</sup>PAK and TO-220**




**Figure 11. Power dissipation vs. case temperature for TO-220FP**




**Figure 12.  $V_{CE(sat)}$  vs. junction temperature****Figure 13.  $V_{CE(sat)}$  vs. collector current****Figure 14. Forward bias safe operating area for D<sup>2</sup>PAK and TO-220****Figure 15. Thermal impedance for D<sup>2</sup>PAK and TO-220****Figure 16. Forward bias safe operating area for TO-220FP****Figure 17. Thermal impedance for TO-220FP**

**Figure 18. Diode  $V_F$  vs. forward current****Figure 19. Gate charge vs. gate-emitter voltage****Figure 20. Capacitance variations vs.  $V_{CE}$** **Figure 21. Switching losses vs. gate resistance****Figure 22. Switching losses vs. collector current****Figure 23. Switching losses vs. temperature**


**Figure 24. Short-circuit time and current vs.  $V_{GE}$** 

### 3 Test circuits


**Figure 25. Test circuit for inductive load switching**




**Figure 26. Gate charge test circuit**



**Figure 27. Switching waveform**



**Figure 28. Diode recovery time waveform**




## 4 Package mechanical data

In order to meet environmental requirements, ST offers these devices in different grades of ECOPACK® packages, depending on their level of environmental compliance. ECOPACK® specifications, grade definitions and product status are available at: [www.st.com](http://www.st.com).  
ECOPACK is an ST trademark.

**Table 9. TO-220FP mechanical data**

| Dim. | mm   |      |      |
|------|------|------|------|
|      | Min. | Typ. | Max. |
| A    | 4.4  |      | 4.6  |
| B    | 2.5  |      | 2.7  |
| D    | 2.5  |      | 2.75 |
| E    | 0.45 |      | 0.7  |
| F    | 0.75 |      | 1    |
| F1   | 1.15 |      | 1.70 |
| F2   | 1.15 |      | 1.70 |
| G    | 4.95 |      | 5.2  |
| G1   | 2.4  |      | 2.7  |
| H    | 10   |      | 10.4 |
| L2   |      | 16   |      |
| L3   | 28.6 |      | 30.6 |
| L4   | 9.8  |      | 10.6 |
| L5   | 2.9  |      | 3.6  |
| L6   | 15.9 |      | 16.4 |
| L7   | 9    |      | 9.3  |
| Dia  | 3    |      | 3.2  |


Figure 29. TO-220FP drawing



**Table 10. TO-220 type A mechanical data**


| Dim. | mm    |       |       |
|------|-------|-------|-------|
|      | Min.  | Typ.  | Max.  |
| A    | 4.40  |       | 4.60  |
| b    | 0.61  |       | 0.88  |
| b1   | 1.14  |       | 1.70  |
| c    | 0.48  |       | 0.70  |
| D    | 15.25 |       | 15.75 |
| D1   |       | 1.27  |       |
| E    | 10    |       | 10.40 |
| e    | 2.40  |       | 2.70  |
| e1   | 4.95  |       | 5.15  |
| F    | 1.23  |       | 1.32  |
| H1   | 6.20  |       | 6.60  |
| J1   | 2.40  |       | 2.72  |
| L    | 13    |       | 14    |
| L1   | 3.50  |       | 3.93  |
| L20  |       | 16.40 |       |
| L30  |       | 28.90 |       |
| ØP   | 3.75  |       | 3.85  |
| Q    | 2.65  |       | 2.95  |

**Figure 30. TO-220 type A drawing**




**Table 11. D<sup>2</sup>PAK mechanical data**

| Dim. | mm   |      |       |
|------|------|------|-------|
|      | Min. | Typ. | Max.  |
| A    | 4.40 |      | 4.60  |
| A1   | 0.03 |      | 0.23  |
| b    | 0.70 |      | 0.93  |
| b2   | 1.14 |      | 1.70  |
| c    | 0.45 |      | 0.60  |
| c2   | 1.23 |      | 1.36  |
| D    | 8.95 |      | 9.35  |
| D1   | 7.50 |      |       |
| E    | 10   |      | 10.40 |
| E1   | 8.50 |      |       |
| e    |      | 2.54 |       |
| e1   | 4.88 |      | 5.28  |
| H    | 15   |      | 15.85 |
| J1   | 2.49 |      | 2.69  |
| L    | 2.29 |      | 2.79  |
| L1   | 1.27 |      | 1.40  |
| L2   | 1.30 |      | 1.75  |
| R    |      | 0.4  |       |
| V2   | 0°   |      | 8°    |

**Figure 31. D<sup>2</sup>PAK drawing**

0079457\_T

**Figure 32. D<sup>2</sup>PAK footprint<sup>(a)</sup>**


Footprint

a. All dimension are in millimeters


## 5 Packaging mechanical data

Table 12. D<sup>2</sup>PAK tape and reel mechanical data

| Tape |      |      | Reel |          |      |
|------|------|------|------|----------|------|
| Dim. | mm   |      | Dim. | mm       |      |
|      | Min. | Max. |      | Min.     | Max. |
| A0   | 10.5 | 10.7 | A    |          | 330  |
| B0   | 15.7 | 15.9 | B    | 1.5      |      |
| D    | 1.5  | 1.6  | C    | 12.8     | 13.2 |
| D1   | 1.59 | 1.61 | D    | 20.2     |      |
| E    | 1.65 | 1.85 | G    | 24.4     | 26.4 |
| F    | 11.4 | 11.6 | N    | 100      |      |
| K0   | 4.8  | 5.0  | T    |          | 30.4 |
| P0   | 3.9  | 4.1  |      |          |      |
| P1   | 11.9 | 12.1 |      | Base qty | 1000 |
| P2   | 1.9  | 2.1  |      | Bulk qty | 1000 |
| R    | 50   |      |      |          |      |
| T    | 0.25 | 0.35 |      |          |      |
| W    | 23.7 | 24.3 |      |          |      |

**Figure 33. Tape**

AM08852v2

**Figure 34. Reel**

AM08851v2

## 6 Revision history

**Table 13. Document revision history**

| Date        | Revision | Changes  |
|-------------|----------|--|
| 03-Oct-2012 | 1        | Initial release.   |
| 18-Mar-2013 | 2        | Added new order code STGF20H60DF, mechanical data <a href="#">Table 9</a> and <a href="#">Figure 29 on page 14</a> .<br>Added <a href="#">Chapter 2.1: Electrical characteristics (curves)</a> .   |
| 22-Mar-2013 | 3        | Document status promoted from preliminary to production data.  |
| 03-Jun-2013 | 4        | Updated $P_{TOT}$ in <a href="#">Table 2: Absolute maximum ratings</a> , $R_{thJC}$ in <a href="#">Table 3: Thermal data</a> and <a href="#">Figure 10: Power dissipation vs. case temperature for D<sup>2</sup>PAK and TO-220</a> .<br>Updated <a href="#">Section 4: Package mechanical data</a> for TO-220. |