



N-channel 600 V, 10 A, very fast IGBT in DPAK package



DPAK



G1C2TE3



Product status link

[STGD10NC60HT4](#)

Product summary

| | |
|-------------------|---------------|
| Order code | STGD10NC60HT4 |
| Marking | GD10NC60H |
| Package | DPAK |
| Packing | Tape and reel |

Features

| Type | V_{CES} | $V_{CE(sat) \text{ max.}}$ | I_C @100°C |
|---------------|-----------|----------------------------|-----------------|
| STGD10NC60HT4 | 600 V | 2.5 V | 10 A |

- Low on-voltage drop ($V_{CE(sat)}$)
- Low CRES / CIES ratio (no cross-conduction susceptibility)

Applications

- High-frequency motor controls
- SMPS and PFC in both hard switch and resonant topologies

Description

This device is a very fast IGBT developed using advanced PowerMESH™ technology. This process guarantees an excellent trade-off between switching performance and low on-state behavior. This device is well-suited for resonant or soft-switching applications.

1 Electrical ratings

Table 1. Absolute maximum ratings

| Symbol | Parameter | Value | Unit |
|----------------|---|------------|------|
| V_{CES} | Collector-emitter voltage ($V_{GE} = 0\text{ V}$) | 600 | V |
| I_C | Continuous collector current at $T_C = 25\text{ °C}$ | 20 | A |
| I_C | Collector current (continuous) at $T_C = 100\text{ °C}$ | 10 | A |
| $I_{CL}^{(1)}$ | Collector current (pulsed) | 40 | A |
| V_{GE} | Gate-emitter voltage | ± 20 | V |
| P_{TOT} | Total power dissipation at $T_C = 25\text{ °C}$ | 60 | W |
| T_J | Operating junction temperature range | -55 to 150 | °C |
| T_{stg} | Storage temperature range | | |

1. $V_{clamp} = 480\text{ V}$, $T_j = 150\text{ °C}$, $R_G = 10\ \Omega$, $V_{GE} = 15\text{ V}$

Table 2. Thermal data

| Symbol | Parameter | Value | Unit |
|----------------|-------------------------------------|-------|------|
| $R_{thj-case}$ | Thermal resistance junction-case | 2.08 | °C/W |
| $R_{thj-amb}$ | Thermal resistance junction-ambient | 62.5 | °C/W |

2 Electrical characteristics

$T_{CASE} = 25\text{ °C}$ unless otherwise specified

Table 3. On/off states

| Symbol | Parameter | Test conditions | Min. | Typ. | Max. | Unit |
|---------------|--|---|------|------|-----------|---------------|
| $V_{(BR)CES}$ | Collector-emitter breakdown voltage | $I_C = 1\text{ mA}$, $V_{GE} = 0\text{ V}$ | 600 | | | V |
| I_{CES} | Collector cut-off current ($V_{GE} = 0\text{ V}$) | $V_{CE} = 600\text{ V}$ | | | 150 | μA |
| | | $V_{CE} = 600\text{ V}$, $T_C = 125\text{ °C}$ ⁽¹⁾ | | | 1 | mA |
| I_{GES} | Gate-emitter leakage current | $V_{GE} = \pm 20\text{ V}$, $V_{CE} = 0\text{ V}$ | | | ± 100 | nA |
| $V_{GE(th)}$ | Gate threshold voltage | $V_{CE} = V_{GE}$, $I_C = 250\text{ }\mu\text{A}$ | 3.75 | | 5.75 | V |
| $V_{CE(sat)}$ | Collector-emitter saturation voltage | $V_{GE} = 15\text{ V}$, $I_C = 5\text{ A}$ | | 1.9 | 2.5 | V |
| | | $V_{GE} = 15\text{ V}$, $I_C = 5\text{ A}$, $T_C = 125\text{ °C}$ | | 1.7 | | |

1. Defined by design, not subject to production test.

Table 4. Dynamic

| Symbol | Parameter | Test conditions | Min. | Typ. | Max. | Unit |
|-----------|------------------------------|---|------|------|------|------|
| C_{ies} | Input capacitance | $V_{CE} = 25\text{ V}$, $f = 1\text{ MHz}$, $V_{GE} = 0\text{ V}$ | - | 365 | - | pF |
| C_{oes} | Output capacitance | | - | 43 | - | pF |
| C_{res} | Reverse transfer capacitance | | - | 8.3 | - | pF |
| Q_g | Total gate charge | $V_{CE} = 390\text{ V}$, $I_D = 5\text{ A}$, $V_{GE} = 0\text{ to }15\text{ V}$ (see Figure 15. Gate charge test circuit) | - | 22 | - | nC |
| Q_{ge} | Gate-emitter charge | | - | 4.5 | - | nC |
| Q_{gc} | Gate-collector charge | | - | 7.5 | - | nC |

Table 5. Switching on/off (inductive load)

| Symbol | Parameter | Test conditions | Min. | Typ. | Max. | Unit |
|----------------|-----------------------|--|--|------|------|------------------|
| $t_{d(on)}$ | Turn-on delay time | $V_{CC} = 390\text{ V}$, $I_C = 5\text{ A}$ $R_G = 10\text{ }\Omega$, $V_{GE} = 15\text{ V}$ | - | 14.2 | - | ns |
| t_r | Current rise time | | - | 5 | - | ns |
| $(di/dt)_{on}$ | Turn-on current slope | (see Figure 14. Test circuit for inductive load switching and Figure 16. Switching waveform) | - | 1000 | - | A/ μs |
| $t_{d(on)}$ | Turn-on delay time | $V_{CC} = 390\text{ V}$, $I_C = 5\text{ A}$ $R_G = 10\text{ }\Omega$, $V_{GE} = 15\text{ V}$, $T_J = 125\text{ °C}$ | - | 14 | - | ns |
| t_r | Current rise time | | - | 5 | - | ns |
| $(di/dt)_{on}$ | Turn-on current slope | | (see Figure 14. Test circuit for inductive load switching and Figure 16. Switching waveform) | - | 920 | - |

| Symbol | Parameter | Test conditions | Min. | Typ. | Max. | Unit |
|------------------|-----------------------|---|------|------|------|------|
| $t_{r(V_{off})}$ | Off voltage rise time | $V_{CC} = 390\text{ V}$, $I_C = 5\text{ A}$, $R_{GE} = 10\ \Omega$, $V_{GE} = 15\text{ V}$ (see Figure 14. Test circuit for inductive load switching and Figure 16. Switching waveform) | - | 27 | - | ns |
| $t_{d(off)}$ | Turn-off delay time | | - | 72 | - | ns |
| t_f | Current fall time | | - | 85 | - | ns |
| $t_{r(V_{off})}$ | Off voltage rise time | $V_{CC} = 390\text{ V}$, $I_C = 5\text{ A}$, $R_{GE} = 10\ \Omega$, $V_{GE} = 15\text{ V}$, $T_J = 125^\circ\text{C}$ (see Figure 14. Test circuit for inductive load switching and Figure 16. Switching waveform) | - | 50 | - | ns |
| $t_{d(off)}$ | Turn-off delay time | | - | 108 | - | ns |
| t_f | Current fall time | | - | 139 | - | ns |

Table 6. Switching energy (inductive load)

| Symbol | Parameter | Test conditions | Min. | Typ. | Max. | Unit |
|-----------------|---------------------------|--|------|-------|------|---------------|
| E_{on} | Turn-on switching energy | $V_{CC} = 390\text{ V}$, $I_C = 5\text{ A}$ $R_G = 10\ \Omega$, $V_{GE} = 15\text{ V}$ (see Figure 14. Test circuit for inductive load switching) | - | 31.8 | - | μJ |
| $E_{off}^{(1)}$ | Turn-off switching energy | | - | 95 | - | μJ |
| E_{ts} | Total switching energy | | - | 126.8 | - | μJ |
| E_{on} | Turn-on switching energy | $V_{CC} = 390\text{ V}$, $I_C = 5\text{ A}$ $R_G = 10\ \Omega$, $V_{GE} = 15\text{ V}$, $T_J = 125^\circ\text{C}$ (see Figure 14. Test circuit for inductive load switching) | - | 61.8 | - | μJ |
| $E_{off}^{(1)}$ | Turn-off switching energy | | - | 173 | - | μJ |
| E_{ts} | Total switching energy | | - | 234.8 | - | μJ |

1. Including the tail of the collector current.

2.1 Electrical characteristics (curves)

Figure 1. Output characteristics




Figure 2. Transfer characteristics




Figure 3. Collector-emitter on voltage vs temperature




Figure 4. Gate charge vs gate-source voltage




Figure 5. Capacitance variations




Figure 6. Normalized gate threshold voltage vs temperature




Figure 7. Collector-emitter on voltage vs collector current




Figure 8. Normalized breakdown voltage vs temperature




Figure 9. Switching energy vs temperature




Figure 10. Switching energy vs gate resistance




Figure 11. Switching energy vs collector current




Figure 12. Thermal Impedance





Figure 13. Turn-off SOA




4 Package information

In order to meet environmental requirements, ST offers these devices in different grades of **ECOPACK®** packages, depending on their level of environmental compliance. ECOPACK® specifications, grade definitions and product status are available at: www.st.com. ECOPACK® is an ST trademark.

4.1 DPAK (TO-252) type A2 package information

Figure 17. DPAK (TO-252) type A2 package outline



0068772_type-A2_rev26

Table 7. DPAK (TO-252) type A2 mechanical data

| Dim. | mm | | |
|------|-------|-------|-------|
| | Min. | Typ. | Max. |
| A | 2.20 | | 2.40 |
| A1 | 0.90 | | 1.10 |
| A2 | 0.03 | | 0.23 |
| b | 0.64 | | 0.90 |
| b4 | 5.20 | | 5.40 |
| c | 0.45 | | 0.60 |
| c2 | 0.48 | | 0.60 |
| D | 6.00 | | 6.20 |
| D1 | 4.95 | 5.10 | 5.25 |
| E | 6.40 | | 6.60 |
| E1 | 5.10 | 5.20 | 5.30 |
| e | 2.159 | 2.286 | 2.413 |
| e1 | 4.445 | 4.572 | 4.699 |
| H | 9.35 | | 10.10 |
| L | 1.00 | | 1.50 |
| L1 | 2.60 | 2.80 | 3.00 |
| L2 | 0.65 | 0.80 | 0.95 |
| L4 | 0.60 | | 1.00 |
| R | | 0.20 | |
| V2 | 0° | | 8° |

4.2 DPAK (TO-252) type C2 package information

Figure 18. DPAK (TO-252) type C2 package outline





Table 8. DPAK (TO-252) type C2 mechanical data

| Dim. | mm | | |
|------|----------|-------|-------|
| | Min. | Typ. | Max. |
| A | 2.20 | 2.30 | 2.38 |
| A1 | 0.90 | 1.01 | 1.10 |
| A2 | 0.00 | | 0.10 |
| b | 0.72 | | 0.85 |
| b4 | 5.13 | 5.33 | 5.46 |
| c | 0.47 | | 0.60 |
| c2 | 0.47 | | 0.60 |
| D | 6.00 | 6.10 | 6.20 |
| D1 | 5.10 | | 5.60 |
| E | 6.50 | 6.60 | 6.70 |
| E1 | 5.20 | | 5.50 |
| e | 2.186 | 2.286 | 2.386 |
| H | 9.80 | 10.10 | 10.40 |
| L | 1.40 | 1.50 | 1.70 |
| L1 | 2.90 REF | | |
| L2 | 0.90 | | 1.25 |
| L3 | 0.51 BSC | | |
| L4 | 0.60 | 0.80 | 1.00 |
| L6 | 1.80 BSC | | |
| θ1 | 5° | 7° | 9° |
| θ2 | 5° | 7° | 9° |
| V2 | 0° | | 8° |


Figure 19. DPAK (TO-252) recommended footprint (dimensions are in mm)



FP_0068772_rev26


4.3 DPAK (TO-252) packing information

Figure 20. DPAK (TO-252) tape outline



AM08852v1

Figure 21. DPAK (TO-252) reel outline



AM06038v1

Table 9. DPAK (TO-252) tape and reel mechanical data

| Tape | | | Reel | | |
|------|------|------|-----------|------|------|
| Dim. | mm | | Dim. | mm | |
| | Min. | Max. | | Min. | Max. |
| A0 | 6.8 | 7 | A | | 330 |
| B0 | 10.4 | 10.6 | B | 1.5 | |
| B1 | | 12.1 | C | 12.8 | 13.2 |
| D | 1.5 | 1.6 | D | 20.2 | |
| D1 | 1.5 | | G | 16.4 | 18.4 |
| E | 1.65 | 1.85 | N | 50 | |
| F | 7.4 | 7.6 | T | | 22.4 |
| K0 | 2.55 | 2.75 | | | |
| P0 | 3.9 | 4.1 | Base qty. | | 2500 |
| P1 | 7.9 | 8.1 | Bulk qty. | | 2500 |
| P2 | 1.9 | 2.1 | | | |
| R | 40 | | | | |
| T | 0.25 | 0.35 | | | |
| W | 15.7 | 16.3 | | | |

Revision history

Table 10. Document revision history

| Date | Version | Changes |
|-------------|---------|------------------|
| 27-Feb-2019 | 1 | Initial release. |

Contents

| | | |
|------------|---|-----------|
| 1 | Electrical ratings | 2 |
| 2 | Electrical characteristics | 3 |
| 2.1 | Electrical characteristics (curves) | 5 |
| 3 | Test circuits | 8 |
| 4 | Package information | 9 |
| 4.1 | DPAK (TO-252) type A2 package information | 9 |
| 4.2 | DPAK (TO-252) type C2 package information | 11 |
| 4.3 | DPAK (TO-252) packing information | 14 |
| | Revision history | 17 |