



STGB8NC60KD - STGD8NC60KD STGF8NC60KD - STGP8NC60KD

600 V - 8 A - short circuit rugged IGBT

Features

- Lower on voltage drop ($V_{CE(sat)}$)
- Lower C_{RES} / C_{IES} ratio (no cross-conduction susceptibility)
- Very soft ultra fast recovery antiparallel diode
- Short circuit withstand time 10 μ s

Applications

- High frequency motor controls
- SMPS and PFC in both hard switch and resonant topologies
- Motor drivers

Description

This IGBT utilizes the advanced PowerMESH™ process resulting in an excellent trade-off between switching performance and low on-state behavior.




Figure 1. Internal schematic diagram



Table 1. Device summary

| Order codes | Marking | Package | Packaging |
|---------------|-----------|--------------------|---------------|
| STGB8NC60KDT4 | GB8NC60KD | D ² PAK | Tape and reel |
| STGD8NC60KDT4 | GD8NC60KD | DPAK | Tape and reel |
| STGF8NC60KD | GF8NC60KD | TO-220FP | Tube |
| STGP8NC60KD | GP8NC60KD | TO-220 | Tube |

Contents

| | | |
|----------|---|-----------|
| 1 | Electrical ratings | 3 |
| 2 | Electrical characteristics | 4 |
| | 2.1 Electrical characteristics (curves) | 7 |
| 3 | Test circuit | 10 |
| 4 | Package mechanical data | 11 |
| 5 | Packaging mechanical data | 15 |
| 6 | Revision history | 17 |

1 Electrical ratings

Table 2. Absolute maximum ratings

| Symbol | Parameter | Value | | | Unit |
|--------------------------------|---|------------------------------|------|----------|------|
| | | D ² PAK TO-220 | DPAK | TO-220FP | |
| V _{CES} | Collector-emitter voltage (V _{GE} = 0) | 600 | | | V |
| I _C ⁽¹⁾ | Collector current (continuous) at T _C = 25 °C | 15 | | 7 | A |
| I _C ⁽¹⁾ | Collector current (continuous) at T _C = 100 °C | 8 | | 4 | A |
| I _{CL} ⁽²⁾ | Turn-off latching current | 30 | | | A |
| I _{CP} ⁽³⁾ | Pulsed collector current | 30 | | | A |
| V _{GE} | Gate-emitter voltage | ±20 | | | V |
| I _F | Diode RMS forward current at T _C = 25 °C | 7 | | | A |
| I _{FSM} | Surge not repetitive forward current t _p = 10 ms sinusoidal | 20 | | | A |
| V _{ISO} | Insulation withstand voltage (RMS) from all three leads to external heat sink (t = 1 s; T _C = 25 °C) | -- | -- | 2500 | V |
| P _{TOT} | Total dissipation at T _C = 25 °C | 65 | 62 | 24 | W |
| T _j | Operating junction temperature | – 55 to 150 | | | °C |
| T _{scw} | Short circuit withstand time (V _{CE} = 0.5 V _{BR(CES)} , T _C = 125 °C, R _G = 10 Ω, V _{GE} = 12 V) | 10 | | | μs |

1. Calculated according to the iterative formula:

$$I_C(T_C) = \frac{T_{JMAX} - T_C}{R_{THJ-C} \times V_{CESAT(MAX)}(T_C) \cdot I_C}$$

- V_{clamp} = 80% (V_{CES}), V_{GE} = 15 V, R_G = 10 Ω, T_J = 150 °C
- Pulse width limited by max junction temperature allowed

Table 3. Thermal resistance

| Symbol | Parameter | Value | | | Unit |
|-----------------------|--|------------------------------|------|----------|------|
| | | D ² PAK TO-220 | DPAK | TO-220FP | |
| R _{thj-case} | Thermal resistance junction-case max IGBT | 1.9 | 2.0 | 5.1 | °C/W |
| R _{thj-case} | Thermal resistance junction-case max diode | 4 | 4.5 | 7 | °C/W |
| R _{thj-amb} | Thermal resistance junction-ambient max | 62.5 | | | °C/W |

2 Electrical characteristics

($T_{CASE}=25^{\circ}C$ unless otherwise specified)

Table 4. Static

| Symbol | Parameter | Test conditions | Min. | Typ. | Max. | Unit |
|----------------|--|--|------|------------|-----------|---------------------|
| $V_{(BR)CES}$ | Collector-emitter breakdown voltage ($V_{GE}=0$) | $I_C=1\text{ mA}$ | 600 | | | V |
| $V_{CE(sat)}$ | Collector-emitter saturation voltage | $V_{GE}=15\text{ V}, I_C=3\text{ A}$ $V_{GE}=15\text{ V}, I_C=3\text{ A}, T_C=125^{\circ}C$ | | 2.2 1.8 | 2.75 | V V |
| $V_{GE(th)}$ | Gate threshold voltage | $V_{CE}=V_{GE}, I_C=250\text{ }\mu\text{A}$ | 4.5 | | 6.5 | V |
| I_{CES} | Collector cut-off current ($V_{GE}=0$) | $V_{CE}=600\text{ V}$ $V_{CE}=600\text{ V}, T_C=125^{\circ}C$ | | | 150 1 | μA mA |
| I_{GES} | Gate-emitter leakage current ($V_{CE}=0$) | $V_{GE}=\pm 20\text{ V}$ | | | ± 100 | nA |
| $g_{fs}^{(1)}$ | Forward transconductance | $V_{CE}=15\text{ V}, I_C=3\text{ A}$ | | 1.9 | | S |

1. Pulse duration = 300 us, duty cycle 1.5 %

Table 5. Dynamic

| Symbol | Parameter | Test conditions | Min. | Typ. | Max. | Unit |
|-----------|------------------------------|---|------|------|------|------|
| C_{ies} | Input capacitance | $V_{CE}=25\text{ V}, f=1\text{ MHz},$ $V_{GE}=0$ | | 380 | | pF |
| C_{oes} | Output capacitance | | | 46 | | pF |
| C_{res} | Reverse transfer capacitance | | | 8.5 | | pF |
| Q_g | Total gate charge | $V_{CE}=390\text{ V}, I_C=3\text{ A},$ | | 19 | | nC |
| Q_{ge} | Gate-emitter charge | $V_{GE}=15\text{ V},$ | | 5 | | nC |
| Q_{gc} | Gate-collector charge | (see Figure 20) | | 9 | | nC |

Table 6. Switching on/off (inductive load)

| Symbol | Parameter | Test conditions | Min. | Typ. | Max. | Unit |
|----------------|-----------------------|---|------|------|------|------------------|
| $t_{d(on)}$ | Turn-on delay time | $V_{CC}=390\text{ V}, I_C=3\text{ A}$ | | 17 | | ns |
| t_r | Current rise time | $R_G=10\text{ }\Omega, V_{GE}=15\text{ V}$ | | 6 | | ns |
| $(di/dt)_{on}$ | Turn-on current slope | (see Figure 21) | | 655 | | A/ μs |
| $t_{d(on)}$ | Turn-on delay time | $V_{CC}=390\text{ V}, I_C=3\text{ A}$ | | 16.5 | | ns |
| t_r | Current rise time | $R_G=10\text{ }\Omega, V_{GE}=15\text{ V},$ $T_C=125^{\circ}C$ | | 6.5 | | ns |
| $(di/dt)_{on}$ | Turn-on current slope | (see Figure 21) | | 575 | | A/ μs |

Table 6. Switching on/off (inductive load) (continued)

| Symbol | Parameter | Test conditions | Min. | Typ. | Max. | Unit |
|----------------|-----------------------|--|------|------|------|------|
| $t_r(V_{off})$ | Off voltage rise time | $V_{CC} = 390\text{ V}, I_C = 3\text{ A},$ | | 33 | | ns |
| $t_{d(off)}$ | Turn-off delay time | $R_{GE} = 10\ \Omega, V_{GE} = 15\text{ V}$ | | 72 | | ns |
| t_f | Current fall time | (see Figure 21) | | 82 | | ns |
| $t_r(V_{off})$ | Off voltage rise time | $V_{CC} = 390\text{ V}, I_C = 3\text{ A},$ | | 60 | | ns |
| $t_{d(off)}$ | Turn-off delay time | $R_{GE} = 10\ \Omega, V_{GE} = 15\text{ V},$ | | 106 | | ns |
| t_f | Current fall time | $T_C = 125\text{ }^\circ\text{C}$ (see Figure 21) | | 136 | | ns |

Table 7. Switching energy (inductive load)

| Symbol | Parameter | Test conditions | Min. | Typ. | Max. | Unit |
|-----------------|---------------------------|--|------|------|------|---------------|
| $E_{on}^{(1)}$ | Turn-on switching losses | $V_{CC} = 390\text{ V}, I_C = 3\text{ A}$ | | 55 | | μJ |
| $E_{off}^{(2)}$ | Turn-off switching losses | $R_G = 10\ \Omega, V_{GE} = 15\text{ V}$ | | 85 | | μJ |
| E_{ts} | Total switching losses | (see Figure 21) | | 140 | | μJ |
| $E_{on}^{(1)}$ | Turn-on switching losses | $V_{CC} = 390\text{ V}, I_C = 3\text{ A}$ | | 87 | | μJ |
| $E_{off}^{(2)}$ | Turn-off switching losses | $R_G = 10\ \Omega, V_{GE} = 15\text{ V},$ | | 162 | | μJ |
| E_{ts} | Total switching losses | $T_C = 125\text{ }^\circ\text{C}$ (see Figure 21) | | 249 | | μJ |

1. E_{on} is the turn-on losses when a typical diode is used in the test circuit in figure 2. If the IGBT is offered in a package with a co-pak diode, the co-pak diode is used as external diode. IGBTs & Diode are at the same temperature (25°C and 125°C)
2. Turn-off losses include also the tail of the collector current

Table 8. Collector-emitter diode

| Symbol | Parameter | Test conditions | Min. | Typ. | Max. | Unit |
|-----------|--------------------------|---|------|------------|------|--------|
| V_F | Forward on-voltage | $I_F = 3\text{ A}$ $I_F = 3\text{ A}, T_C = 125\text{ }^\circ\text{C}$ | | 1.6 1.3 | 2.1 | V V |
| t_{rr} | Reverse recovery time | $I_F = 3\text{ A}, V_R = 30\text{ V},$ | | 23.5 | | ns |
| Q_{rr} | Reverse recovery charge | $di/dt = 100\text{ A}/\mu\text{s}$ | | 16.5 | | nC |
| I_{rrm} | Reverse recovery current | (see Figure 22) | | 1.4 | | A |
| t_{rr} | Reverse recovery time | $I_F = 3\text{ A}, V_R = 30\text{ V},$ | | 39 | | ns |
| Q_{rr} | Reverse recovery charge | $T_C = 125\text{ }^\circ\text{C}, di/dt = 100\text{ A}/\mu\text{s}$ | | 39 | | nC |
| I_{rrm} | Reverse recovery current | (see Figure 22) | | 2 | | A |

2.1 Electrical characteristics (curves)

Figure 2. Output characteristics




Figure 3. Transfer characteristics




Figure 4. Transconductance




Figure 5. Collector-emitter on voltage vs temperature




Figure 6. Gate charge vs gate-source voltage




Figure 7. Capacitance variations




Figure 8. Normalized gate threshold voltage vs temperature




Figure 9. Collector-emitter on voltage vs collector current




Figure 10. Normalized breakdown voltage vs temperature




Figure 11. Switching losses vs temperature




Figure 12. Switching losses vs gate resistance




Figure 13. Switching losses vs collector current




Figure 14. Thermal impedance for TO-220/D²PAK




Figure 15. Turn-off SOA




Figure 16. Forward voltage drop versus forward current




Figure 17. Thermal impedance for DPAK





Figure 18. Thermal impedance for TO-220FP



3 Test circuit

Figure 19. Test circuit for inductive load switching




Figure 20. Gate charge test circuit




Figure 21. Switching waveform





Figure 22. Diode recovery time waveform




4 **Package mechanical data**

In order to meet environmental requirements, ST offers these devices in ECOPACK® packages. These packages have a lead-free second level interconnect. The category of second level interconnect is marked on the package and on the inner box label, in compliance with JEDEC Standard JESD97. The maximum ratings related to soldering conditions are also marked on the inner box label. ECOPACK is an ST trademark. ECOPACK specifications are available at: www.st.com


TO-220 mechanical data

| Dim | mm | | | inch | | |
|-----|-------|-------|-------|-------|-------|-------|
| | Min | Typ | Max | Min | Typ | Max |
| A | 4.40 | | 4.60 | 0.173 | | 0.181 |
| b | 0.61 | | 0.88 | 0.024 | | 0.034 |
| b1 | 1.14 | | 1.70 | 0.044 | | 0.066 |
| c | 0.48 | | 0.70 | 0.019 | | 0.027 |
| D | 15.25 | | 15.75 | 0.6 | | 0.62 |
| D1 | | 1.27 | | | 0.050 | |
| E | 10 | | 10.40 | 0.393 | | 0.409 |
| e | 2.40 | | 2.70 | 0.094 | | 0.106 |
| e1 | 4.95 | | 5.15 | 0.194 | | 0.202 |
| F | 1.23 | | 1.32 | 0.048 | | 0.051 |
| H1 | 6.20 | | 6.60 | 0.244 | | 0.256 |
| J1 | 2.40 | | 2.72 | 0.094 | | 0.107 |
| L | 13 | | 14 | 0.511 | | 0.551 |
| L1 | 3.50 | | 3.93 | 0.137 | | 0.154 |
| L20 | | 16.40 | | | 0.645 | |
| L30 | | 28.90 | | | 1.137 | |
| ∅P | 3.75 | | 3.85 | 0.147 | | 0.151 |
| Q | 2.65 | | 2.95 | 0.104 | | 0.116 |




TO-252 (DPAK) mechanical data

| DIM. | mm. | | |
|------|------|------|-------|
| | min. | typ | max. |
| A | 2.20 | | 2.40 |
| A1 | 0.90 | | 1.10 |
| A2 | 0.03 | | 0.23 |
| b | 0.64 | | 0.90 |
| b4 | 5.20 | | 5.40 |
| c | 0.45 | | 0.60 |
| c2 | 0.48 | | 0.60 |
| D | 6.00 | | 6.20 |
| D1 | | 5.10 | |
| E | 6.40 | | 6.60 |
| E1 | | 4.70 | |
| e | | 2.28 | |
| e1 | 4.40 | | 4.60 |
| H | 9.35 | | 10.10 |
| L | 1 | | |
| L1 | | 2.80 | |
| L2 | | 0.80 | |
| L4 | 0.60 | | 1 |
| R | | 0.20 | |
| V2 | 0° | | 8° |



D²PAK (TO-263) mechanical data

| Dim | mm | | | inch | | |
|-----|------|------|-------|-------|-------|-------|
| | Min | Typ | Max | Min | Typ | Max |
| A | 4.40 | | 4.60 | 0.173 | | 0.181 |
| A1 | 0.03 | | 0.23 | 0.001 | | 0.009 |
| b | 0.70 | | 0.93 | 0.027 | | 0.037 |
| b2 | 1.14 | | 1.70 | 0.045 | | 0.067 |
| c | 0.45 | | 0.60 | 0.017 | | 0.024 |
| c2 | 1.23 | | 1.36 | 0.048 | | 0.053 |
| D | 8.95 | | 9.35 | 0.352 | | 0.368 |
| D1 | 7.50 | | | 0.295 | | |
| E | 10 | | 10.40 | 0.394 | | 0.409 |
| E1 | 8.50 | | | 0.334 | | |
| e | | 2.54 | | | 0.1 | |
| e1 | 4.88 | | 5.28 | 0.192 | | 0.208 |
| H | 15 | | 15.85 | 0.590 | | 0.624 |
| J1 | 2.49 | | 2.69 | 0.099 | | 0.106 |
| L | 2.29 | | 2.79 | 0.090 | | 0.110 |
| L1 | 1.27 | | 1.40 | 0.05 | | 0.055 |
| L2 | 1.30 | | 1.75 | 0.051 | | 0.069 |
| R | | 0.4 | | | 0.016 | |
| V2 | 0° | | 8° | 0° | | 8° |



TO-220FP mechanical data

| Dim. | mm. | | | inch | | |
|------|-------|-----|-------|-------|-------|-------|
| | Min. | Typ | Max. | Min. | Typ. | Max. |
| A | 4.40 | | 4.60 | 0.173 | | 0.181 |
| B | 2.5 | | 2.7 | 0.098 | | 0.106 |
| D | 2.5 | | 2.75 | 0.098 | | 0.108 |
| E | 0.45 | | 0.70 | 0.017 | | 0.027 |
| F | 0.75 | | 1.00 | 0.030 | | 0.039 |
| F1 | 1.15 | | 1.50 | 0.045 | | 0.067 |
| F2 | 1.15 | | 1.50 | 0.045 | | 0.067 |
| G | 4.95 | | 5.20 | 0.195 | | 0.204 |
| G1 | 2.40 | | 2.70 | 0.094 | | 0.106 |
| H | 10 | | 10.40 | 0.393 | | 0.409 |
| L2 | | 16 | | | 0.630 | |
| L3 | 28.6 | | 30.6 | 1.126 | | 1.204 |
| L4 | 9.80 | | 10.60 | 0.385 | | 0.417 |
| L5 | 2.9 | | 3.6 | 0.114 | | 0.141 |
| L6 | 15.90 | | 16.40 | 0.626 | | 0.645 |
| L7 | 9 | | 9.30 | 0.354 | | 0.366 |
| Dia | 3 | | 3.2 | 0.118 | | 0.126 |



5 Packaging mechanical data

D²PAK FOOTPRINT



TAPE AND REEL SHIPMENT

TAPE MECHANICAL DATA

| DIM. | mm | | inch | |
|------|------|------|--------|--------|
| | MIN. | MAX. | MIN. | MAX. |
| A0 | 10.5 | 10.7 | 0.413 | 0.421 |
| B0 | 15.7 | 15.9 | 0.618 | 0.626 |
| D | 1.5 | 1.6 | 0.059 | 0.063 |
| D1 | 1.59 | 1.61 | 0.062 | 0.063 |
| E | 1.65 | 1.85 | 0.065 | 0.073 |
| F | 11.4 | 11.6 | 0.449 | 0.456 |
| K0 | 4.8 | 5.0 | 0.189 | 0.197 |
| P0 | 3.9 | 4.1 | 0.153 | 0.161 |
| P1 | 11.9 | 12.1 | 0.468 | 0.476 |
| P2 | 1.9 | 2.1 | 0.075 | 0.082 |
| R | 50 | | 1.574 | |
| T | 0.25 | 0.35 | 0.0098 | 0.0137 |
| W | 23.7 | 24.3 | 0.933 | 0.956 |

REEL MECHANICAL DATA

| DIM. | mm | | inch | |
|------|------|------|-------|--------|
| | MIN. | MAX. | MIN. | MAX. |
| A | | 330 | | 12.992 |
| B | 1.5 | | 0.059 | |
| C | 12.8 | 13.2 | 0.504 | 0.520 |
| D | 20.2 | | 0.795 | |
| G | 24.4 | 26.4 | 0.960 | 1.039 |
| N | 100 | | 3.937 | |
| T | | 30.4 | | 1.197 |

| BASE QTY | BULK QTY |
|----------|----------|
| 1000 | 1000 |

10 pitches cumulative tolerance on tape +/- 0.2 mm

Center line of cavity

User Direction of Feed

FEED DIRECTION

Bending radius R min.

* on sales type

DPAK FOOTPRINT



TAPE AND REEL SHIPMENT

40 mm min. Access hole at slot location

Full radius

Tape slot in core for tape start 2.5mm min. width

G measured at hub

REEL MECHANICAL DATA

| DIM. | mm | | inch | |
|------|------|------|-------|--------|
| | MIN. | MAX. | MIN. | MAX. |
| A | | 330 | | 12.992 |
| B | 1.5 | | 0.059 | |
| C | 12.8 | 13.2 | 0.504 | 0.520 |
| D | 20.2 | | 0.795 | |
| G | 16.4 | 18.4 | 0.645 | 0.724 |
| N | 50 | | 1.968 | |
| T | | 22.4 | | 0.881 |

TAPE MECHANICAL DATA

| DIM. | mm | | inch | |
|------|------|------|-------|-------|
| | MIN. | MAX. | MIN. | MAX. |
| A0 | 6.8 | 7 | 0.267 | 0.275 |
| B0 | 10.4 | 10.6 | 0.409 | 0.417 |
| B1 | | 12.1 | | 0.476 |
| D | 1.5 | 1.6 | 0.059 | 0.063 |
| D1 | 1.5 | | 0.059 | |
| E | 1.65 | 1.85 | 0.065 | 0.073 |
| F | 7.4 | 7.6 | 0.291 | 0.299 |
| K0 | 2.55 | 2.75 | 0.100 | 0.108 |
| P0 | 3.9 | 4.1 | 0.153 | 0.161 |
| P1 | 7.9 | 8.1 | 0.311 | 0.319 |
| P2 | 1.9 | 2.1 | 0.075 | 0.082 |
| R | 40 | | 1.574 | |
| W | 15.7 | 16.3 | 0.618 | 0.641 |

BASE QTY | **BULK QTY**

2500 | 2500

10 pitches cumulative tolerance on tape +/- 0.2 mm

Center line of cavity

User Direction of Feed

FEED DIRECTION

Bending radius

6 Revision history

Table 9. Document revision history

| Date | Revision | Changes |
|-------------|----------|---|
| 02-Oct-2007 | 1 | First release |
| 01-Apr-2008 | 2 | Updated Figure 14 and Figure 17 |