



		1		
Part Number:		DRAWN	2/12/2017	
CM20	0408-1	CJ	3/13/2017	
SVV381		CHECKED	10/5/2017	
		P.D.		
Description:	namic Speaker	APPROVED	10/5/2017	
waterproof Dy		C.E.	10/5/2017	

This document contains data proprietary to DB Unlimited. Any use or reproduction, in any form, without prior written permission of DB Unlimited is prohibited. All terms and conditions can be found at www.dbunlimitedco.com


Top View



Side View



Bottom View



Items	Specifications	Conditions					
Sound Pressure Level	90	dB (@ 10cm), Avg.					
Resonant Frequency	400	Hz					
Frequency Range	400 ~ 10,000	Hz					
Nominal Power	2	W	REVISION HISTORY				
Max. Power	2.5	W	REV	DESCRIPTION	DATE	APPROVED	
Impedance	8	Ω		Released from Engineering	10/5/2017	C.E.	
Cone Material	Mylar		NOTES				
Mount Type	Flush Mount		1) All dimensions are in mm unless otherwise noted				
IP Rating	IP67		2) All tolerances are ± 0.3 mm unless otherwise noted				
Storage Temperature	-20 ~ +55	°C	3) All parts meet RoHS				
Operating Temperature	-20 ~ +55	°C	4) Subject to change or redrawn without notice				
Weight	7.9	g					
	<u> </u>	2		2		1	