


Dual Inline AUI Isolation Transformer



Thru-Hole DIL AUI Isolation Transformer



Product Features:


- Designed for AUI Ports
- UL/EN60950 Recognized
- 100% Compliance Testing
- 1500Vrms Hi-Pot
- RoHS Compliant

Part Number	OCL ($\mu\text{H} \pm 20\%$)	Turns Ratio	Rise Time (ns max)	PRI Cw/w (pF max)	PRI LL (μH max)	DCR (Ω max)	Temp. Range
TD01-0506KRL	50	1:1	3ns	10	0.20	0.20	0 to 70°C
TD01-0756KRL	75	1:1	3ns	10	0.20	0.20	0 to 70°C
TD01-1006KRL	100	1:1	3ns	10	0.20	0.20	0 to 70°C
TD01-1506KRL	150	1:1	3ns	10	0.20	0.20	0 to 70°C


Notes:

1. Please contact the factory or representative for individual datasheets or additional information

Circuit



Mechanical



Dimensions: inch [mm]



2880 Lakeside Drive #116
Santa Clara, CA 95054
(650) 903-3800
www.haloelectronics.com

HALO® Electronics is a leading supplier of high quality communication magnetics including signal transformers, filters, CMR chokes, PoE power transformers, DC/DC converters, and integrated Ethernet connectors. HALO's leading edge technology solutions are manufactured in ISO9001 and ISO14001 factories offering high quality products at a competitive price.

© Copyright 2014 HALO Electronics, Inc. All rights reserved.

Revised 8/2014. Download the latest version at www.haloelectronics.com/pdf/discrete-dil-aui.pdf