


Specifications			Notes	Revision History																
Description	Value	Unit		Version	Description	Date	Approved													
Technology	Electro-Mechanical		1) All dimensions are in mm unless otherwise noted 2) All parts meet RoHS <div style="text-align: center;">  DB UNLIMITED </div>	1	Released from Engineering	10/21/2013	J.S													
Resonant Frequency	2,731	(Hz)																		
Rated Voltage	3.5	(V)																		
SPL @ 10cm	85	(dBA)																		
Coil Resistance	25	(ohm)																		
Mount Type	Thru Hole																			
Voltage Range	2 ~ 4	(V)																		
Max Rated Current	60	(mA)																		
Housing Material	NORYL																			
Operating Temperature	-30 ~ +70	°C																		
Storage Temperature	-40 ~ +85	°C																		
Weight	1	(g)																		
			Electro-Mechanical Transducer	TE092703-4																
			<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="text-align: left;">Drawn by</th> <th style="text-align: left;">Date</th> <th style="text-align: left;">Checked by</th> <th style="text-align: left;">Date</th> <th style="text-align: left;">Approved by</th> <th style="text-align: left;">Date</th> </tr> </thead> <tbody> <tr> <td>A.B.</td> <td>10/21/2013</td> <td>C.E.</td> <td>10/21/2013</td> <td>J.S</td> <td>10/21/2013</td> </tr> </tbody> </table>		Drawn by	Date	Checked by	Date	Approved by	Date	A.B.	10/21/2013	C.E.	10/21/2013	J.S	10/21/2013				
Drawn by	Date	Checked by	Date	Approved by	Date															
A.B.	10/21/2013	C.E.	10/21/2013	J.S	10/21/2013															

Additional considerations can be found at www.dbunlimitedco.com/technical-articles.