


T1/E1 Isolation Modules

SMD Dual Port or Quad Channel T1/E1 Transformers



US Patent Numbers:
5,656,985 6,297,721 B1
6,297,720 B1 6,320,489 B1
6,344,785 B1 6,662,431 B1

Product Features:

- T1/E1/CEPT/ISDN-PR
- UL/EN60950/DEMKO Recognized
- 100% Electrical Testing
- 1500Vrms Hi-Pot
- Patented Open Frame Construction

Part Number	Circuit	Turns Ratio PRI:SEC	PRI OCL (mH typ)	Temp. Range	Primary Pins	RoHS ¹
TG05-1205NM5LF	A	1:2	1.2	0 to 70°C	1-2, 3-4, 6-7, 8-9	Pb-Free
TG05-1205NM5RL	A	1:2	1.2	0 to 70°C	1-2, 3-4, 6-7, 8-9	RoHS (7a)
TG07-1205NM5LF	B	1:2CT & 1:2CT	1.2	0 to 70°C	20-19, 15-14 & 4-5, 9-10	Pb-Free
TG07-1205NM5RL	B	1:2CT & 1:2CT	1.2	0 to 70°C	20-19, 15-14 & 4-5, 9-10	RoHS (7a)
TG23-1205NM5LF	A	1:2.42	1.2	0 to 70°C	1-2, 3-4, 6-7, 8-9	Pb-Free
TG23-1205NM5RL	A	1:2.42	1.2	0 to 70°C	1-2, 3-4, 6-7, 8-9	RoHS (7a)
TG25-1205NM5LF	A	1:1.26	1.2	0 to 70°C	1-2, 3-4, 6-7, 8-9	Pb-Free
TG25-1205NM5RL	A	1:1.26	1.2	0 to 70°C	1-2, 3-4, 6-7, 8-9	RoHS (7a)
TG27-S003NM5LF	B	1:2CT & 1:1.36CT	1.2	0 to 70°C	20-19, 15-14 & 4-5, 9-10	Pb-Free
TG27-S003NM5RL	B	1:2CT & 1:1.36CT	1.2	0 to 70°C	20-19, 15-14 & 4-5, 9-10	RoHS (7a)
TG36-1205NM5LF	A	1:1.15 & 1:1	1.2	0 to 70°C	1-2, 6-7 & 18-17, 13-12	Pb-Free
TG36-1205NM5RL	A	1:1.15 & 1:1	1.2	0 to 70°C	1-2, 6-7 & 18-17, 13-12	RoHS (7a)
TG37-1205NM5LF	B	1:1.14CT	1.2	0 to 70°C	20-19, 4-5, 15-14, 9-10	Pb-Free
TG37-1205NM5RL	B	1:1.14CT	1.2	0 to 70°C	20-19, 4-5, 15-14, 9-10	RoHS (7a)
TG39-1205NM5LF	A	1:1.15	1.2	0 to 70°C	1-2, 3-4, 6-7, 8-9	Pb-Free
TG39-1205NM5RL	A	1:1.15	1.2	0 to 70°C	1-2, 3-4, 6-7, 8-9	RoHS (7a)
TG42-1205NM5LF	A	1:√2	1.2	0 to 70°C	1-2, 18-17, 6-7, 8-9	Pb-Free
TG42-1205NM5RL	A	1:√2	1.2	0 to 70°C	1-2, 18-17, 6-7, 8-9	RoHS (7a)
TG49-1205NM5LF	B	1CT:2 & 1:2CT	1.2	0 to 70°C	1-3, 6-8 & 4-5, 9-10	Pb-Free
TG49-1205NM5RL	B	1CT:2 & 1:2CT	1.2	0 to 70°C	1-3, 6-8 & 4-5, 9-10	RoHS (7a)
TG83-1205NM5LF	A	1:2 & 1:1	1.2	0 to 70°C	1-2, 6-7 & 18-17, 13-12	Pb-Free
TG83-1205NM5RL	A	1:2 & 1:1	1.2	0 to 70°C	1-2, 6-7 & 18-17, 13-12	RoHS (7a)
TGSP-S125NM5LF	A	1:2.4 & 1:1	1.2	0 to 70°C	1-2, 8-9 & 3-4, 6-7	Pb-Free
TGSP-S125NM5RL	A	1:2.4 & 1:1	1.2	0 to 70°C	1-2, 8-9 & 3-4, 6-7	RoHS (7a)


Notes:

1. Pb-Free parts are RoHS 6/6 compliant. RoHS (7a) parts contain lead per exemption 7a which is set to expire in July 2016.
2. Parts with RL suffix are not recommended for new designs.
3. Please contact the factory or representative for individual datasheets or additional information.


For additional information contact your [local representative](#), or HALO's support staff at (650) 903-3800 or info@haloelectronics.com

HALO Gigabit Family of Ethernet Transformers




Circuit A




Circuit B



NM5 Package



Dimensions: inch [mm]
 Co-Planarity: 0.004 [0.10]



Recommended Solder Pad Layout



2880 Lakeside Drive #116
 Santa Clara, CA 95054
 (650) 903-3800
www.haloelectronics.com

HALO® Electronics is a leading supplier of high quality communication magnetics including signal transformers, filters, CMR chokes, PoE power transformers, DC/DC converters, and integrated Ethernet connectors. HALO's leading edge technology solutions are manufactured in ISO9001 and ISO14001 factories offering high quality products at a competitive price.